

PATENT APPLICATION SERIAL NO. _____

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

09455409

12/16/1999 GDUCKETT 00000005 012135 09455409

| | | |
|-----------|---------|-----------|
| 01 FC:201 | | 380.00 OP |
| 02 FC:203 | 9.00 CH | 171.00 OP |

Please type a plus sign (+) inside this box → ☒

PTO/SB/05 (12/97)
Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

12/06/99

1685 U.S. PTO

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 780.29643CX4

Total Pages

First Named Inventor or Application Identifier

Thomas J. CAMPANA, Jr. et al

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patent
Box Patent Application
Washington, DC 20231

1. ☒ Fee: \$551.00

Please charge any shortages in the fees or credit any overpayments thereof to the deposit account of Antonelli, Terry, Stout & Kraus, Deposit Account No. 01-2135.

6. ☐ Microfiche Computer Program (Appendix)

7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)

- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

2. ☒ Specification (w/12 pg. Appendix) Total Pages 99

3. ☒ Drawing(s) (35 USC 113) Total Sheets 12

4. Oath or Declaration Total Pages 3

- a. ☐ Newly executed (original or copy)
- b. ☒ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below]

i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☒ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

ACCOMPANYING APPLICATION PARTS

- 8. ☒ Assignment Papers (cover sheet & document(s)) (Copy of prev. Assg. 4 pgs.)
- 9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
- 10. ☐ English Translation Document (if applicable)
- 11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations
- 12. ☒ Preliminary Amendment & IDS copies & Sub. Appendix (54 pages)
- 13. ☐ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
- 14. ☐ Small Entity ☒ Statement filed in prior application. Status still proper and desired
- 15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
- 16. ☒ Other: Change of Address
Change of Correspondence Address
Submission of Formal Drawings.

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: 09, 161, 462

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

020457

(Insert Customer No. or Attach bar code label here)

11. SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME Donald E. Stout

SIGNATURE 

DATE December 6, 1999

REG. NO. 26,422

ANTONELLI, TERRY, STOUT & KRAUS, LLP

SUITE 1800

1300 NORTH SEVENTEENTH STREET
ARLINGTON, VIRGINIA 22209

TELEPHONE
(703) 312-6600
FACSIMILE
(703) 312-6666
E-MAIL
email@antonelli.com

A system (100) for transmitting information from one of a plurality of originating processors A-N to at least a plurality of destination processors (A-N) which may be transported during operation in accordance with the invention includes at least one gateway switch (14), a gateway switch storing information received from one of the at least one originating processor prior to transmission of the information to the at least one destination processor; a RF information transmission network (302) for transmitting stored information received from one of the at least one gateway switch by RF transmission to at least one destination processor; at least one interface switch (304), an interface switch connecting a gateway switch to the RF transmission network and transmitting stored information received from one of the at least one gateway switch to the RF information transmission network; and wherein the information is transmitted to a receiving interface switch by the electronic mail system in response to an address of the receiving interface switch which has been added to the information originated by the originating processor by either the originating processor or gateway switch and the information is transmitted from the receiving interface switch to the RF information transmission network with an address of the destination processor to receive the information which has been added by either the originating processor, a gateway switch or the receiving interface switch.

CL

Cross-Reference to Related Applications

Reference is made to other applications ~~which are filed on even date herewith which are~~ incorporated by reference in their entirety.

5

Ins.
A₁

United States Patent Application Serial No. ~~_____~~, entitled "Electronic Mail System With RF Communications to Mobile Processors Originating From Outside of the Electronic Mail System" ~~(Attorney Docket No. 780.29766X00)~~; and

A
A

10

Ins.
A₂

United States Patent Application Serial No. ~~_____~~, entitled "System for Interconnecting Electronic Mail Systems By RF Communications" ~~(Attorney Docket No. 780.29767X00)~~;

Ins.
A₃

0055400-12039
0055400-12039

2

Description
Electronic Mail System With RF
Communications to Mobile Processors

CL Technical Field

5 The present invention relates to electronic mail systems for transmitting information between processors.

CL Background Art

10 The use of computers to send and receive electronic mail messages is becoming very popular globally. Numerous companies (both network and software related) offer electronic mail packages (E Mail) and services. Currently, electronic mail services provide a convenient alternative to the more
 15 formal facsimile transmissions of memos and documents. Electronic mail is typically used to send relatively short informal messages between computers within an organization, or to a party located at a distant location or company. Electronic mail services are
 20 basically a wire line-to-wire line, point-to-point type of communications. Electronic mail, similar to facsimile transmissions, provides a one-way message. A recipient typically does not have to interact with the message. Electronic mail, unlike facsimile, is a
 25 non-real-time message transmission architecture.

 Fig. 1 illustrates a block diagram of a typical electronic mail system 10 in commercial use such as by AT&T Corporation. The electronic mail system 10 is
 30 comprised of a plurality of single processors or groups of processors #1-#N with N being any number with each group having individual processors A-N with N being any number. The groups of processors #1-#N may be distributed at locations which are linked by the public

switch telephone network 12. The individual processors may be portable personal computers with a modem which are linked to the public telephone switch network 12 through wired or RF communications as indicated by a dotted line. Groups of associated processors #1-#3 may have diverse configurations with the illustrated configurations only being representative of possible architectures of groups of associated processors. The groups of associated processors may be connected to a host or mainframe computer through various communication mechanisms such as direct telephone communications (#1), communications through a local area network (#2), or communications through a private automatic branch exchange (#3). It should be understood that the illustrated architecture of the single and associated groups of processors is only representative of the state of the art with numerous variations being utilized. Many of the groups of associated processors are contained within the database network of a single company or organization located at distributed geographical locations throughout a country or in different countries.

Communications between an originating processor A-N, which may be any of the processors within the groups of associated processors #1-#3 or processor #N and a destination processor A-N are completed through the public switch telephone network 12 to one or more gateway switches with mailboxes 14 which function to store the message for delivery to the destination processor at a later point in time. The gateway switches with mailboxes 14 have a storage location, associated with each subscriber which may be any of the computers A-N within the associated groups of computers #1-#3 and individual computers #N, which provides retrieval capability of the electronic message

when it is not delivered directly to the destination processor A-N such as when the destination processor does not go directly off hook in response to an attempt to deliver the message from storage in the electronic mail gateway mailbox storage location associated with the destination processor. In order to originate an electronic mail message, the originating processor A-N calls an associated gateway switch with mailboxes 14 via telephone through the usage of a modem connection. This connection is made through the public switch network 12. A gateway switch with mailboxes 14 answers and provides a data connection to the originating processor A-N. The gateway switch with mailboxes 14 typically contains the originating processor A-N file and verifies that the sending processor is able to originate an electronic mail message via some form of password protection. Upon verification of the entry password, the electronic gateway switch with mailboxes 14 down loads software and entry screens that are displayed on the originating processor to permit a message to be composed. Thereafter, the message is composed and transferred from the originating processors gateway switch with mailboxes 14 to the destination processors gateway switch with mailboxes where the message is stored and an attempt is made to deliver the message to the destination processor via telephone connection through the public switch telephone network 12.

Electronic mail systems have several common items that must be entered in order to originate and send (format) an electronic message. These items include the destination address, which consists of either the person or company's name, an abbreviated form of the person's company or name, or a series of digits or alphanumeric characters that must be entered to

66302T 60455460
66302T 60455460

indicate to the electronic mail system the destination address of the recipient processor. Another item is an identification of the originating processor which may be an indication of the sender or the originator's name, company name, an abbreviated form of the originator's name or company name, or a numeric or alphanumeric entry that comprises the sender's name or address. This information is collectively an identification of the originating processor. Another item is the subject of the message which is typically a short reference as to the subject matter of the text or message that follows. Finally, the message or message text must be entered which is the information that is inputted by the person or machine which is originating the message at the originating processor A-N. Upon completion of the message text, the user or machine operating the originating processor A-N enters a series of commands or keystrokes on the originating processor to transmit the message to the gateway switch with mailboxes 14 associated with the originating processor A-N.

The transmission of the message from the originating processor's gateway switch with mailboxes 14 to the destination processor's electronic mail gateway switch with mailboxes is via analog or digital communications through the public switch telephone network. The destination gateway switch with mailboxes 14 contains the destination address of the recipient destination processor.

Upon arrival of the information at the destination processor's gateway switch with mailboxes 14, one of two events takes place. The information is typically stored in the destination processor's electronic mailbox for later retrieval by the destination processor through interaction by the user of the

6

destination processor. This typically happens as a result of the fact that a person is not located at the destination processor at the time of delivery of the message to the gateway switch with mailboxes 14 or the destination processor is not turned on and connected to the public switch telephone network 12. A second methodology is that the destination processor's gateway switch with mailboxes automatically dials the gateway processor's telephone number to deliver the information. In the situation where the destination processor is within a company or organization, the information may be delivered to the host computer. The destination processor's host computer stores the information until the destination processor calls the host computer to retrieve the information. In both of the methodologies described above, information delivery requires periodically calling a host computer or a mailbox at the gateway switch with mailboxes 14 to determine if new messages are present. This incurs additional costs in telephone calls and/or labor. If the host computer or gateway switch is not checked frequently, the information becomes untimely in its delivery. If the destination processor frequently checks the host computer or gateway switch, then additional costs and telephone calls and/or labor are encountered.

As personal computers are used more frequently by business travellers, the problem of electronic mail delivery becomes considerably more difficult. A business traveller carrying a portable PC has great difficulty in finding^a telephone jacks to connect the PC to fetch electronic mail from either a host computer or a gateway switch. Connections for a PC's modem are difficult to find in airports and with the advent of digital PABX's in businesses ~~and~~ the telephone

connectors are incompatible with a PC's analog modem. Hotels and motels oftentimes have internal PABX's that prevent calls from automatically being placed by the user's PC to electronic mail gateway switches to retrieve information. Most portable PC modems will only operate correctly when connected to a true outside telephone line that has telephone battery voltages and dial tone available to permit the number to be dialed direct. The inability to find an appropriate connection to connect the PC modem when travelling has contributed to the degradation of electronic mail reception when the recipient is travelling. When travelling internationally, this problem is further compounded by the fact that most electronic mail gateway mailboxes require a 1-800 toll free number ^{to be} ~~is~~ dialed in order to connect the mailbox. Almost all 1-800 telephone numbers are available for continental use only and cannot be accessed from a foreign country.

Industry trends make it increasingly difficult to receive electronic mail. When PC's were exclusively considered an office or desktop machine, it was less difficult to deliver electronic mail. Advances in the state of the art in microelectronics have permitted PC's to be downsized to very lightweight portable (notebook), and notebook size computers. These portable units have the computing and storage power of the former desktop units and have lent themselves to the trend that they now become very portable in their utilization. They are small enough that they can easily fit into an attache case and/or a suit pocket. The net result is that the portable unit no longer resides in the office or the desktop. The portable unit now may be taken home at night, as well as on travel with the user, such as for business travel.

Increased portability of PC's further aggravates the problem of automatic electronic mail delivery as a consequence of portability eliminating the wired communication paths which have been typically used in state of the art electronic mail systems. The electronic mail industry is currently experiencing a rapid growth rate.

Numerous communication companies are offering forms of electronic mail services. However, a problem arises that users of one electronic mail system currently cannot send electronic mail to a subscriber of another electronic mail system (e.g., AT&T E-mail to Sprint Mail, etc.). Numerous attempts are currently underway in the industry to solve this problem. Current attempts are the utilization of common protocols between electronic mail systems (e.g. X.400). However, the proposed system does not resolve the problems resultant from portability and travelling situations described above.

Fig. 2 illustrates a diagram of a prior art network 100 developed by Telefind Corporation of Coral Gables, Florida, which provides ⁹worldwide paging and data transmission capability and is a preferred form of the RF information transmission network used in practicing the present invention. This network is described in detail in ~~the Assignee's~~ United States Patents 4,866,431, 4,868,558, 4,868,562, 4,868,860, 4,870,410, 4,878,051, 4,881,073, 4,875,039 and 4,876,538 and United States patent application Serial Nos. 409,390, 464,675, 465,894, 464,680, 429,615, 429,541, 409,605, and 456,742 which are incorporated herein by reference in their entirety. The system ⁴²⁴is a distributed network of switches comprised of a plurality of local switches 112, a plurality of lata switches 114 and a plurality of hub switches 116 with

9

each switch being located in a different geographical location within an area being serviced by the system. The hub switches 116 may be located totally within a country to provide national service or in multiple countries to provide international service. Only a single portion of the network is labelled with reference numerals with it being understood that repeating portions exist such as for that portion under the jurisdiction hub switch #P. Communication links which are illustrated as a dotted arrow represent network structure which has been omitted for clarity that is identical to structure that is illustrated in detail. Additionally, one or more sublocal switches may optionally be provided within the system under the jurisdiction of the local switch as described in the aforementioned patents. The sublocal switches have been omitted for purposes of clarity. Each switch has jurisdiction over a geographic area. The functions performed by the local switch 112, the data switch 114 and the hub switch 116 are described below. A local paging service 118 is typically connected to each of the local switches 112 which offers other paging services ~~than that provided by the present invention~~ although it should be understood that the local switch may be used exclusively to control all services offered at the local level. The local paging service 118 is typically an existing common carrier paging service which services an area within broadcast distance of a transmitter 115 under the jurisdiction of the local paging service to which the local switch 112 has been connected to permit the local paging service to function in the network to transmit pages to a plurality of paging receivers 119 (only one having been illustrated) connected to a peripheral device 119 which may be a data processor printer, telex service,

0445409.12069
0045409

A

facsimile service or other types of data processing
 devices. The paging receivers automatically download
 data stored in their memory upon connection to a
 printer for producing a printout of the data. The
 printer ^{was} ~~is~~ sold with the receiver by Telefind
 Corporation of Coral Gables, Florida. The paging
 receivers 119 are described in United States Patents
 4,849,750, 4,851,830, 4,853,688, 4,857,915, 4,928,100,
 4,935,732, 4,978,944 and 5,012,235 and United States
 Patent application Serial Nos. 381,483, 381,527,
 597,350 and 662,616 which ^{were} ~~are~~ assigned to Telefind
 Corporation of Coral Gables, Florida. The transmitter
 115 may be either an analog or digital transmitter.
 Communications between the local, lata and hub switches
 may be by any existing communication medium 120 such as
 direct dial-up circuits (IDD Circuits International),
 direct outward dial circuits (end-to-end), in-bound
 watts (and other in-bound services that are volume
 discounted), out-bound watts (and other out-bound
 services that are volume discounted), feature group A
 (U.S. service), feature group B (U.S. and European
 services), MF tie trunks (U.S. and European services),
 and direct inward dial (international service, where
 available), as well as any future medium which permits
 pages to be transmitted between switches. Each of
 these services are indicated schematically by a
 bi-directional arrow 120 which interconnects a local
 switch 112 to a lata switch 114, a lata switch to a hub
 switch 116, and a hub switch to another hub switch.
 Furthermore, the local switches 112 are connected to a
 local paging service 118 by a communication link 122 of
 any conventional nature, including wires connecting the
 local switch to the local paging service. Each switch
 is provided with a local telephone trunk 127 which
 functions as a maintenance port. Furthermore, dotted

669021 "6045546
 669021 "6045546

//

bi-directional lines 124 illustrate alternative communication paths between switches which may be used in the case of malfunction or busy conditions. It should be further understood that the network is not limited to any particular communication protocol linking switches, nor connecting the local switch to the local paging service. A telephone trunk 28 functions as an input for manual (telephone handset) and automatic device entry of pages as described below.

The network 110 provides numeric, alphanumeric and data services to all points within the United States and participating countries. In the preferred embodiment of the network, a universal code is used for encoding transmissions of characters over both the communication links 120 and 122 which is compatible with existing analog and digital transmitters 115. A universal code discussed in the aforementioned patents utilizes sixteen tones for encoding all characters for transmission between switches or to a local paging service 118. Each character is transmitted as two successive tones. A X.25 modified transmission protocol which is disclosed in the aforementioned network patents is preferably utilized for transmitting packets of pages between switches.

The network 110 is economical to implement and operate as a consequence of utilizing distributed processing technologies and transmission of pages periodically in packets of pages between the switches. Dynamic interaction between a frequency agile pager, which preferably is of the type described in the above-referenced receiver patents and applications and the network 110 efficiently utilizes transmission time that is available in the frequency spectrum. One of the distinct advantages of the network 110 is that it utilizes existing paging common carriers to deliver

66002T 62455460
66002T 62455460

A

12

pages to the end user with existing paging RF coverage in the United States being greater than 85% of its geographical area with just two 150 MHz frequencies with a total of 10,500 additional frequencies being available for paging receiver use. Wire line common carriers, private systems, hospital, government, emergency and many other services can be accommodated by the utilization of dynamic frequency programming, by the network 110 to change the frequency band on which individual paging receivers may receive pages.

The network 110 provides an integrated sublocal, local, regional and nationwide paging network that is transparent to use by the subscriber and provides for pages (data transmissions) to be called into an existing local paging service 118 by the making of a local phone call on a telephone trunk 128 connected to the local switch 112 in a conventional fashion as well as to any lata switch 114 throughout the network 110 by a local phone call to telephone trunk 126. The functionality of permitting pages or data transmissions to be originated anywhere within the network 10 by local telephone call, preferably by calling a single number within the country (950-XXXX) avoids the telephone expense and system overhead caused by calling of a central switch to originate a page. It should be understood that the network's usage of periodically transmitting packets of pages between switches results in a much lower cost than the cost of 800 or conventional long distance service. The phone trunk 126 for calling the lata switch 114 to place a page anywhere within the network 110 is indicated by bi-directional arrows to each lata switch. Regardless of the location of the person making the telephone call to a lata switch 114 over telephone trunk 126 to originate a page, the lata switch will formulate a page

with the destination specified by geographically descriptive digits of the identification code inputted with the call to request a page or data transmission to the lata switch and the network 110 will automatically route the page through the switches of the network to the person being paged by way of the local switch 112, which stores a subscriber file that stores the identification code of the subscriber and paging receiver. The local switch 112, which stores the identification code inputted with the page in its subscriber file, adds one or more destinations to the page and transmits the page(s) to the local paging service 118 and/or the network 110 by way of the lata switch 114 having jurisdiction. The person placing the page by calling the local switch 112 on telephone trunk 128 or the lata switch 114 on telephone trunk 126 does not have to know the location of the person receiving the page.

The local switch 112 is connected to a participating common carrier paging service 118 located in a particular geographic area. The local switch 112 has local direct inward dial trunks 128 which permits the subscriber to use a local telephone call to place a page. Pages over the local telephone trunks 128 may be (1) numeric characters which are entered manually by DTMF tones or other telephone coding mechanisms, (2) alphanumeric characters which are entered manually by DTMF tones or other coding mechanisms, (3) alphanumeric characters which are entered by an automatic message inputting device using an encoding format having a transmission protocol of conventional nature such as DTMF tones or (4) a high speed (baud rate) encoding protocol such as an X.25 protocol permitting a variable number of pages or data transmissions each with its own network destination to

be formed into a packet which is transmitted to a single switch. The local switch 12 has voice prompting which facilitates the person placing a call on the telephone trunk 28 to enter a message to be transmitted as a page.

The local switch 112 processes the pages received from the telephone trunk 128 and from the associated lata switch 114 to which the local switch is connected by the communication link 120. It should be understood that the local switch 112 has programming which automatically and dynamically monitors paging traffic when a plurality of transmission frequencies are used and allocates the frequencies available to the paging service 118 for transmission to the paging receivers to maximize the local paging services paging throughput as described below. The local switch 112 calls the resident local paging terminal of the paging service 118 and determines how much air time it has to deliver a batch of pages to the transmitter 115 associated with the local paging service. The local switch 112 then calls the local paging terminal of the local paging service 118 and transmits a batch of pages encoded in the hybrid encoding format described below which is compatible with existing analog and digital FM paging transmitters.

The local switch periodically transmits packets of pages or data transmissions stored in an outbound lata buffer over communication link 20 to the lata switch 114 having jurisdiction over it which provides cost efficient transmission and efficient page or data transmission processing. This architecture is highly efficient in routing the pages originating at the local switch 112 to be transmitted by the network 110 which are intended for broadcast by a transmitter remote from the local switch having a subscriber file storing the

identification code of the subscriber to which data or a page is to be transmitted.

When the subscriber desires to receive regional, national, or international service, the local data switch 112 is programmed by the subscriber by simple telephone area code entries which identify the service areas to which pages or data transmissions are to be transmitted. The programming is accomplished by adding or deleting one or more area codes of the subscriber's destination field contained in a subscriber file maintained in the subscriber's local switch 112. In the United States, area codes are used for ease of subscriber use and telephone books may then serve as the service area directory. The same ease of use is available to worldwide customers with county-city code entries available from telephone books in any airport, hotel or business.

The local switch controls the generation of individual pages or data transmissions having message detail as described below with reference to Fig. 6. The number of pages or data transmissions which are generated in response to a page received without an area destination from the telephone trunk 128 or from a data switch 114 is determined by the central processor of the local switch 112 interrogating any area destinations listed in the destination area code field of the local switch as described below with reference to Fig. 3. Each page or data transmission generated by the processor contains the same message content. A separate page or data transmission is generated for each destination area listed in the destination area code field and if the local service option of the service option field is selected, as described below, an additional page or data transmission is generated for broadcast by the local

paging service 118 without an area destination in the
 network which is processed by the local switch 112 as a
 page or data transmission received from the network for
 broadcast by the local paging service. Furthermore,
 5 each individual page or data transmission generated by
 a local switch 12 contains one or more commands. The
 commands which are added to each page or data
 transmission transmitting a message are determined by
 the operation of the central processor of the local
 10 switch 112 in response to interrogation of the selected
 service options of the subscriber. Programming of
 receivers with the channel programming command is in
 response to the local switch programming the receiver
 to receive one or more channels, subscriber programming
 15 of destination areas of reception in the destination
 area code field, and the degree of utilization of the
 channels of the local transmitter 115.

The central processor of the local switch 112
 processes each individual page or data transmission
 20 received from the network to determine if it originated
 from a local switch 112 or a lata switch 114. This
 determination is made by determining if a destination
 header identifying a lata switch 114 originating the
 page precedes the paging receiver identification code
 25 in a packet having the configuration of Fig. 6. In the
 absence of the header (which is a geographic
 identification of the originating lata switch 112 in
 the network) in an individual page or data
 transmission, the page or data transmission is
 30 processed exclusively by the local switch 112 for
 broadcast by the associated local paging service 118
 without interrogation of a subscriber file in the local
 switch. If the header is found in a page or data
 transmission, the central processor processes the page
 35 as either a request to reprogram the subscriber file or

A
 as a page received on the telephone port 128 without an area destination which must be processed to determine one or more area destinations ^{be} ~~and~~ formed into new pages each with a different area destination from the area destination field if transmission by the network is to occur and into a page or data without an area destination if transmission by the local service 18 is to occur.

5
 10 The local switch 112 also serves as the dynamic programming interface between the paging or data receivers 119 and the network 110. The local paging service 18 may cause channels to be received by receivers 19, change subscriber identification codes and add new customers to the network 110 utilizing the
 15 the local switch 112. The functionality of the receiver 119 can be changed from a fixed channel to a multi-channel or a scanning receiver as required by use of the channel programming command.

20 Messages originating at the local switch 112 which are transmitted to the data collector switch 114 having jurisdiction over it are packetized as described below with reference to Fig. 6. Destination area codes (telephone area codes or other geographically descriptive code) are added to pages or data
 25 transmissions prior to transmission to the data switch 114 and the receiver 119 is dynamically and automatically reprogrammed for the new service areas by the local switch 112 issuing channel programming command(s) which ensures that the receiver 119 is
 30 programmed to receive channels in each designated area. The current channels remain in the receiver 119 to avoid loss of a message while a subscriber is still in the area.

5 The lata switch 114 provides a second tier of
network intelligence. This intelligence includes page
or data transmission processing, packetizing and
routing. The lata switch 114 receives packets of pages
10 from each of the local switches 112 within its
jurisdiction as well as the hub switch 116 having
jurisdiction over it. The lata switch 114 provides the
geographical presence for the network 110 to originate
and terminate pages or data transmissions utilizing
15 dial-up or dedicated communication services.

20 The lata switch 114 is responsible for collection
of pages from the local switches 112 within its
jurisdiction. When a packet of pages is received from
the local switch 112, it is disassembled, processed and
15 stored for transmission to the proper destination(s) in
one or more packets each consisting of one or more
pages which are intended for destination(s) either
within or outside the lata switch jurisdiction. The
lata switch 114 periodically transmits packets of pages
20 stored in its outbound hub buffer and its outbound
local buffer to the associated hub switch 116 having
jurisdiction over it and to local switches 112 within
its jurisdiction which provides cost efficient
transmission and efficient processing by avoiding
25 processing by a single central switch controlling the
network 110. This architecture is highly efficient in
routing pages or data transmissions originating within
the jurisdiction of the lata switch 114 which are
intended for broadcast outside its jurisdiction as well
30 as distributing pages or data transmissions from one
local switch 112 to one or more additional local
switches within the jurisdiction of the lata switch.
If the page or data transmission is destined for
distribution within the jurisdiction of the lata
35 switch 114, the page or data transmission is processed

into packets for transmission to each of the local switches 112 within its jurisdiction or alternatively to less than all of the local switches in its jurisdiction. The pages or data transmissions are then
 5 periodically transmitted as packets to the local switches 112 within the jurisdiction of the data switch 114.

The data switch 114 is also responsible for collection of pages outside its jurisdiction to be
 10 broadcast to the local switches 112 within its jurisdiction. Packets received from the hub switch 116 are disassembled, processed, and packetized for transmission to the destination local switches 112.

The function of the data switch 114 in collecting requests for placing pages or data transmissions in the network or to reprogram the subscriber file of a local switch 112 by placing a local phone call on telephone trunk 126 is an important aspect of the network.
 15 ~~Invention.~~ The data switch 114 places the header discussed above, which geographically identifies the data switch originating the page or data transmission in front of the receiver identification code, in a packet as illustrated in the message detail of Fig. 6 to enable the local switch 112 to differentiate between
 20 pages or data transmission which are for broadcast by the local service 118 associated with a receiving local switch 112 and pages or data transmission which require access to the subscriber files to generate one or more pages or data transmissions for broadcast or for
 25 reprogramming a subscriber file. Preferably, the header is four digits comprised of a country code followed by the telephone area code identifying the data switch 114 which received the call for the
 30 originating page or data transmission.

The hub switch 116 provides the third tier of network intelligence and serves as an inter-regional communications link. One hub switch 116 will preferably be located in each international region to serve as a network routing switch. In the United States, a hub switch 116 will be located within the region served by each of the Bell regional companies (RBOC's). Accordingly, in the United States the preferred implementation of the network 110 includes seven distinct hub switches 116. Each hub switch 116 in a preferred embodiment can have fifty-five lata switches 114 under its jurisdiction. The hub switch 116 also serves as a network routing switch for inter-hub calls when pages or data transmissions are to continue in the hub-to-hub network.

When a packet of pages is received from either another hub switch 116 or a lata switch 114 within its jurisdiction, the pages or data transmission are disassembled for examination. Each page or data transmission is examined for its destination address(es). A determination is made if the hub switch 116 should forward the page or data transmission to one of the six adjacent hub switches or forward the page or data transmission to a lata switch 114 within its jurisdiction. The pages or data transmissions are then destination processed and packetized for transmission to either another hub switch 116 or a lata switch 114 within its jurisdiction.

Fig. 3 illustrates a memory map of the RAM of a local switch 112. The RAM has four main storage areas which are the subscriber files 154, channel files 156, lata buffers 158 and local buffers 160.

5 Each local switch 112 is allocated a capacity of, for example, 10,000 subscribers which are identified by a four-digit code stored in field 162 of the subscriber files 154.

10 Field 164 stores the subscriber's local telephone number within the area code serviced by the lata switch 114 having jurisdiction.

15 Field 166 is the subscriber's receiver identification code which uniquely identifies the subscriber and the receiver 119 of the subscriber which is to receive pages or data transmissions throughout the network 110. The receiver identification number (code) consists of 8 digits with the four most significant digits geographically representing the area serviced by the associated lata switch 114 (country code as the most significant digit followed sequentially by area or city code lesser significant digits) and the four least significant digits being digits assigned to identify 10,000 subscribers within the jurisdiction of the local switch. The capacity of
20 the network 110 is 100 million subscribers with the eight digit identification code. The least significant numbers of the identification code define subscribers of a specific local switch 112 within the jurisdiction of the lata switch 114.
25

30 Field 168 stores the service options which each subscriber may choose to have provided by the local service 118. The service options control the commands, which are used with pages or data transmissions sent to the receivers 119. The main CPU interrogates the
35 particular subscriber file identified by the

identification code inputted with the request for a page or data transmission by telephone trunks 126 or 128, causes storage of the page or data transmission, determines the destination(s) of the page or data transmission and the appropriate system command to be used to transmit the page or data transmission. It should be understood that the service options may be dynamically programmed through voice prompted communications over the telephone trunk lines 128 with the local switch 112 and through telephone calls to the lata switch 114 by trunk 126 as described below.

The service options are described as follows. The service option "a" is for no service which is a condition when an active subscriber does not wish to receive any pages or data transmissions such as may occur when the subscriber is on vacation or is otherwise desirous of not being reached for a period of time but does not wish to be removed from the subscriber base of the system. The service option "b" is for pages or data transmissions to be broadcast only by the transmitter 115 of the local service 118. The service option "c" is for regional service which is for pages or data transmissions to be broadcast throughout all of the local services 118 which are within its lata switch jurisdiction. The service option "d" is for national service which is for pages or data transmissions to be broadcast from the local switch 112 to one or more lata switches 114 other than the lata switch having jurisdiction over the local switch. While not illustrated, an international service option may be added. The service option "e" is for a repeat of pages or data transmissions for any of the "b", "c" or "d" service options so that a page or data transmission is broadcast more than once. The service option "f" is for data service which causes the page or

data transmission to be stored in a specified section of the receiver memory. The service option "g" is for external data service which commands the receiver 119 to output the page or data transmission to the external data port of the receiver. This option permits the receiver 119 to support peripheral devices such as printers or processors to provide a wide range of data services.

The following additional fields are provided. The fifth field 170 is the subscriber's name and the subscriber's specified account number. The sixth field 172 is the subscriber's account number entry for purposes of interval billing by the local service 118. The seventh field 174 is the subscriber's count (local, regional or national) which is a total of the number of pages or data transmissions made in a billing period. The eighth field 176 is the total number of data characters sent during the billing period.

The ninth field 178 is the destination (area code(s)) of each of the pages or data transmissions. For local service, there is no area code specified. For regional service, the area code of the associated data switch 114 having jurisdiction over the local switch 112 is specified and for national and international service, one or more area codes or other geographic identification identifying data switches other than the data switch having jurisdiction over the local switch are specified. For international service, a country code may be used to identify data switches 114 within a particular country. Any number of area codes may be specified but in a preferred embodiment of the network 110, three area codes is a maximum number of data switches 114 which may be specified as regions to receive pages from the local switch 112.

5 The above-referenced description describes the first file of the n (10,000) possible subscriber files stored in the subscriber files 154. It should be understood that the other subscriber files have the same configuration. Access to the subscriber file is obtained by a voice prompted message requiring the inputting of a secret code which if inputted correctly is followed by voice prompted requests requesting specification of the information of the subscriber file to be changed.

10 The frequency files 156 perform an important function in the network 110. The frequency files 156 contain n possible lata files with each individual file identifying up to, for example, 15 four-digit numbers that represent broadcast channels available within the service area of a lata switch 114. Thus, each of the individual lata switches 114 in the network 110 will have a separate frequency file which identifies all of the channels which are available to transmit pages or data transmissions from the transmitters 115 associated with the local services 118 under the jurisdiction of that lata switch 114. The channels are stored as a four-digit number in a hexadecimal numbering system which requires only four digits of space. A file containing all zeros (no channel) will cause an invalid area code message to be returned to a subscriber attempting to reprogram service areas. The frequency files are the source of channels which are utilized by the channel programming command to program each receiver 119 for operation in each lata switch jurisdiction and the local switch jurisdiction. For example, a receiver 119 which is to be serviced by only a single local service 118 may be programmed to receive only a single or a number of channels up to the number of channels used by that local paging service.

Furthermore, for regional service or national service,
 the frequency files 156 are used to program the
 receiver 119 to receive pages or data transmissions
 from the channels used by the local services 118 within
 5 the designated area codes representative of the service
 areas serviced by the data switches 114. Furthermore,
 if a receiver 119 is to be programmed to receive
 messages in a particular area serviced by a data
 switch 114 as a consequence of the subscriber
 10 travelling, the channel programming command utilizes
 the channels stored in the file number corresponding to
 the jurisdiction of the data switch 114 in the area to
 which the subscriber is to travel, to dynamically
 program the channel(s) which the paging receiver is to
 15 receive in that area. For service in a local region,
 the frequency files are used as a source of channels to
 be used by the channel programming command to
 dynamically shift the channels on which the paging
 receiver is to receive a page, to adjust the channels
 20 used in the broadcast area used by the local
 service 118 associated with the local switch 112 based
 on the amount of traffic on each channel and to further
 provide a source of channels which are to be used for
 specialized services for transmitting particular types
 25 of information to particular subscribers such as, but
 not limited to stock quotations.

The data buffers 158 consist of an inbound data
 buffer 180 and an outbound data buffer 182. The
 inbound data buffer 180 functions to receive pages or
 30 data transmissions coded in ASCII which have been
 processed to strip the X.25 transmission protocol used
 for transmitting pages from the data switch 114 to the
 local switch 112 and converted from the hybrid code
 described below to ASCII. Pages or data transmissions
 35 which are initially stored in the inbound data

26

buffer 180 are processed for destination and are either for broadcast by the associated local service 118 in which case they are ultimately stored in the appropriate identification code buffer 186 which matches the least significant digit of the identification code contained with the page or data transmission or in the outbound data buffer 182 if the page or data transmission originated from one of the data switches 114 by calling on the telephone trunk 126 and which has a final destination which is determined by the field 178 of the subscriber file 154.

The local buffers 160 are comprised of an inbound buffer 184 for receiving all local inbound pages or data transmissions which originate from the trunk line 128 which is connected to the local switch 112 and a plurality of identification code buffers 186 which are each individually assigned to store outbound pages or data transmissions with a particular least significant identification code digit of the number base used for the subscriber identification code which are to be transmitted to a receiver 119. All of the received pages or data transmissions from the local switch 112 are initially stored in the buffer 184. Each of the individual identification code buffers 186 stores pages or data transmissions for broadcast by the local service 118 in batches which are grouped by the least significant digit of the subscriber identification code received with the page or data transmission after sorting by the CPU. In other words, the least significant digit of the subscriber identification code within a page or data transmission for broadcast by a local service 118 determines in which of the identification code buffers 186 the page or data transmission is stored. For example, if the last digit of the identification code of a page or data

transmission for broadcast by the local service 118 ends in the digit 0, the page or data transmission is stored in the identification code buffer identified by "0".

5 Fig. 4 is a memory map of the random access memory of the lata switch 114. The random access memory has three main areas and two optional areas. The three main areas are hub buffers 188, local buffers 190 and a
10 lata identification code (ID) memory 192. The optional memory areas are an all call buffer 194 for storing nationwide pages or data transmissions received from the hub switch 116 which are to be transmitted to all of the local switches 112 under the jurisdiction of the
15 lata switch 114 and an all call buffer 196 which stores pages or data transmissions received from one of the local switches 112 which are to be transmitted to all of the local switches under the jurisdiction of the lata switch 114.

The hub buffers 188 are an outbound hub buffer 198
20 and an inbound hub buffer 200. The outbound hub buffer 198 stores pages or data transmissions to be periodically transmitted to the hub switch 116 having jurisdiction over the lata switch 114 under the control of the CPU. The inbound hub buffer 200 stores pages or
25 data transmissions which are periodically received from the associated hub switch 116 via storage in a buffer of the CPU.

The local buffers 190 are comprised of an inbound
30 local buffer 202 which stores groups of inbound pages or data transmissions received from the local switches 112 and a plurality of outbound local buffers 204 each of which store groups of pages or data transmissions which are to be transmitted periodically to a specific one of the local switches with a separate
35 outbound local buffer being provided for each of the

A
 5 local switches under the jurisdiction of the lata switch 114. The CPU processes each of the pages or data transmissions which is received in the inbound buffers 200 and 202 by destination and causes storage in the outbound buffers 198 and 204 which is associated with the destination of the page or data transmission.

10 The lata identification code memory 192 stores the subscriber identification numbers of all of the subscribers which are associated with each of the local switches 112 within its jurisdiction. The lata identification code memory 192 is used for determining the local switch 112 which stores a subscriber file of the subscriber used for pages or data transmissions which are inputted to the system from a direct call by
 15 telephone trunk 126 to a lata switch 114 or from a direct call by telephone trunk 126 to a lata switch by a subscriber to program the reception area of pages or data transmissions by changing the destination 178 of the pages or data transmissions. The lata
 20 identification code memory 192 may be organized by subscriber identification codes which are within the jurisdiction of each local switch 112 so that the matching of an identification code of a page or data transmission inputted to the lata switch 114 in the
 25 lata identification code memory 192 provides the location of the particular local switch which stores the subscriber file 154 of that subscriber.

30 In order to avoid having to provide additional storage space in each of the outbound local buffers 204, the optional all call buffer 194 may be provided to store a single page or data transmission, received from the hub switch 116 having jurisdiction over the lata switch 114, which is to be transmitted to each of the local switches 112. Similarly, the
 35 optional all call buffer 196 may be provided for

29

receiving pages or data transmissions from an individual local switch 112 which are to be transmitted to all of the local switches within the jurisdiction of the lata switch 114.

5 For pages, data transmissions or requests to reprogram the subscriber file 154 which are made to a lata switch 114 over telephone trunk 126 which require access to a subscriber file outside the jurisdiction of the lata switch, the CPU forms a page or data
10 transmission contained in a packet having an area destination identified by the four most significant digits of the identification code inputted to the lata switch 114 preceded by the identification code of the receiver 119 to receive the page or data transmission,
15 preceded by the geographical area identification of the lata switch receiving the call to originate a page or data transmission or to program the subscriber file which is transmitted by the network 110 to the specified area destination. For pages or data
20 transmissions to be billed to subscribers stored in the subscriber file 154 of a local switch 112 within the jurisdiction of the lata switch 114 or requests to program the subscriber file 154, the CPU forms a packet having an area destination of the local switch 112
25 within its jurisdiction which stores the subscriber identification code as determined by interrogation of the lata identification code buffer 192 by the CPU. The ultimate destination of a page or data transmission is determined by the destination field 178 of the
30 subscriber file 154 matching the identification code of the receiver 119 either within or outside the jurisdiction of the lata switch that is called in over telephone trunk 126. The local switch 112 containing the subscriber file 154 creates the one or more pages
35 or data transmissions in accordance with the

information in the subscriber file including the adding of destination(s) and the appropriate command. Transmission of the pages or data transmissions created by the local switch 112 in response to a call to a data switch 114 is identical to the transmission of pages or data transmissions originating at the local switch 112 by the placing of a telephone call on telephone trunk 128. In the case of requesting programming of the subscriber's file 154, the caller must in response to a voice prompted message enter a four-digit secret identification code to obtain access to the subscriber file with voice prompted messages being supplied under the control of the CPU to control the input of programming information from the subscriber. To request a page or data transmission by calling the data switch 114, the caller will receive a voice prompted message to enter the subscriber identification code and then the appropriate page or data transmission.

Fig. 5 is a memory map of the random access memory of the hub switch 116. The hub switch memory map is comprised of four main parts which are hub buffers 206, data buffers 208, data code tables 210 and hub routing codes 212. The hub buffers 206 are comprised of a plurality of inbound hub buffers 214 which correspond in number to the number of other hub switches 116 in the network 110 which have direct connection to the hub switch and a corresponding number of outbound hub buffers 216. The individual inbound hub buffers 214 each store pages or data transmissions received from one of the hub switches 116 with pages or data transmissions received from each adjacent hub switch 116 being stored in only a single one of the inbound hub buffers 214. Similarly, pages or data transmissions which are to be transmitted to another hub switch 116 are stored in the outbound hub

buffer 216 which is associated with the destination hub
 switch to which they are being transmitted with all
 pages or data transmissions which are to be routed to a
 single hub switch being stored in a corresponding one
 5 of the outbound hub buffers 216 with a separate hub
 buffer being associated with each hub switch to which
 pages or data transmissions are directly transmitted.
 The lata buffers 208 are comprised of a plurality of
 inbound lata buffers 218 which correspond to the number
 10 of lata switches 114 under the jurisdiction of the hub
 switch 116. The inbound lata buffers 218 store all of
 the pages or data transmissions received from the lata
 switches 114 under the jurisdiction of the hub
 switch 116. The outbound lata buffers 220 correspond
 15 in number to the lata switches 114 under the
 jurisdiction of the hub switch 116 with a separate lata
 buffer being associated with each of the lata
 switches. The outbound lata buffers 220 store groups
 20 of pages or data transmissions to be periodically
 transmitted to their associated lata switch 114. Pages
 or data transmissions which are stored in the inbound
 hub buffers 214 are processed by destination by the CPU
 and stored in either the outbound hub buffer 216, which
 is the destination of the pages or data transmissions
 25 not to be received by a lata switch 114 under the
 jurisdiction of the hub switch 116, or in one or more
 of the outbound lata buffers 220 if the destination of
 the packets received from another hub switch 116 is a
 lata switch under the jurisdiction of the hub switch.
 30 The CPU also processes the pages or data transmissions
 stored in the inbound lata buffers 218 according to
 their destination and causes their storage in either
 the outbound hub buffers 216 if the pages or data
 transmissions are to be sent to a lata switch 114
 35 outside of the jurisdiction of the hub switch 116 or to

32

one or more of the outbound lata switches 220 if the pages or data transmissions are to be received by one or more lata switches 114 under the jurisdiction of the hub switch 116.

5 The lata code tables 210 store each of the lata (telephone area or other geographic identifier) codes 222 under the jurisdiction of the hub switch 116 which are utilized by the comparison performed by the CPU with the pages or data transmissions stored in the
10 inbound hub buffers 214 and inbound lata buffers 218 to determine in which of the outbound hub buffers 216 or outbound lata buffers 220 the pages or data transmissions should be stored. Each separate lata code 222 corresponds to the geographical identification
15 of the lata switch 114 which in the preferred embodiment is the telephone area code of a lata switch's jurisdiction.

 The routing codes 212 determine the transmission routes to other hub switches on a priority basis to
20 which a packet should be sent which are not intended for a lata switch 114 within the jurisdiction of the hub switch 116. It should be understood that a number of factors may be considered in choosing the priority of a route to be used to transmit a packet from one hub switch 116 to another hub switch. It would appear on
25 first analysis that a direct first hub switch to second hub switch route would be best but often the switching overhead of routing a packet through one or more intermediate switches is more than compensated for by
30 the efficiency of a route having one or more intermediate hub switches by adding additional pages or data transmissions to the packet which are inputted to the one or more intermediate hub switch(es) to the packets being transmitted to the second hub switch.
35 The CPU compares the destination of the groups of pages

or data transmissions stored in the inbound hub buffers 214 and the inbound data buffers 218 to determine if these pages or data transmissions should be routed to another hub switch 116. The hub routing codes 212 are referred to by default when a match is not found by the CPU in comparing the destination of the pages or data transmissions stored in the inbound hub buffers 214 and inbound data buffers 218 with the codes stored in the data code tables 210. Each page or data transmission stored in the inbound hub buffer 214 and inbound data buffers 218 is processed by destination by the CPU and caused to be stored in the outbound buffers 216 and 220 which correspond to its destination. Each individual hub routing code contains the hub switch destination priorities for pages or data transmissions to be sent to a single data switch 114 outside the jurisdiction of the hub switch 116. For example, for the data switch 114 having jurisdiction over area code 312, the hub routing code 234 determines the priorities in descending order from the highest priority to the lowest priority such that the highest priority hub would be #1 followed by #2-#6.

Fig. 6 illustrates a preferred transmission protocol to be used for transmitting packets between switches. The protocol which is used is a modified X.25 protocol. As illustrated, each packet contains five separate layers. The first layer is the destination telephone number which is the receiving port to receive the page or data transmission. With reference to Fig. 2 if a packet of X.25 formatted pages or data transmissions were to be sent from a first data switch 114 to its associated hub switch 116 over communication path 120, the destination telephone number would be the telephone number of the hub switch. It should be further understood that the X.25

transmission protocol as described herein may be utilized with other types of communication mediums between switches such that a destination telephone number may be replaced with another form of address of the receiving switch. The second layer indicates the packet size field in terms of succeeding layers of information. In the present case levels 3, 4 and 5 are provided which dictates that the packet size would store the number 3 to indicate the subsequently lower third, fourth and fifth layers. The third layer contains an origination switch address and a destination switch address which can be either telephone numbers or real addresses within the network 110. The fourth layer is the number of pages or data transmissions which are contained in a packet. As illustrated, this number may be any integer n. The fifth layer is one or more pages or data transmissions which each correspond to an individual page or data transmission to be sent to a particular receiver 119.

Each message includes the following information. In accordance with standard X.25 protocol, a beginning of file header is included. Following the beginning of file header is a receiver I.D. code which is the identification code of the destination receiver which is identical to the subscriber identification code stored in the subscriber files 154 of the subscriber to receive the page or data transmission. Following the I.D. code is the destination(s) of the page or data transmission which is geographically descriptive of the area to which the page or data transmission is to be transmitted and is added by the local switch 112 interrogating the destination field 178 of Fig. 3. In the preferred embodiment, the destination is a combination of country and area code as utilized by the telephone system to identify the area to which the page

or data transmission is destined. For each country, the same country code will be used so that if the system 110 as illustrated in Fig. 1 were to be utilized for the United States, the first digit of the destination would be a 1. Similarly, the destinations in other countries would be followed by different numbers identifying those countries followed by code which breaks up the identified country into smaller geographic regions. ~~While the utilization of area codes under the telephone system facilitates the usage of the present invention, it~~ should be understood that a destination which is not based on the telephone system is equally usable ~~with the present invention~~. The field of special commands are the system commands which are transmitted with each page or data transmission to a receiver. The "page" or "data transmission" is the part which is to be displayed to the bearer of the receiver 119 and may be numeric or alphanumeric characters. The end of the file and file size information are part of a standard X.25 protocol.

Fig. 7 illustrates an interconnection between a paging receiver (left side) in accordance with the above-referenced receiver patents and a printer (right side) which has been offered for sale by Telefind Corporation of Coral Gables, Florida. The "EXTERNAL ANTENNA" pin is for connection only to an external antenna and connects the RF signal from the external antenna to the receiver internal antenna. The "LINK" pin is detected by the printer to determine if the receiver 119 is connected or not. If the receiver is not connected when peripheral power is on, then the CPU of the printer will detect that the "LINK" pin is high. Otherwise the "LINK" pin will be low. The pin "EXTERNAL BUZZER" outputs a 2KHz trigger signal when a page or data transmission is received. The

"EXTERNAL BUZZER" pin also outputs the 2KHz trigger
 signal when display of a message is complete. The pin
 "PRG VCC" is supplied 5 volt power by the attached
 printer to provide power to the receiver 119 whether
 5 the pager is powered or not. The "GROUND" pin is
 ground for the printer and receiver 119. The pin
 "BUSY" is pulled high by the printer if the printer is
 too busy to handle input data bits on the "PRTDATA" pin
 10 of the receiver 119. The "PRTDATA" pin is the data
 output from the receiver 119 to the printer. Serial
 data bits are fed to the printer to drive the printer
 to generate text corresponding to the data bits. The
 "DIS AUDIO" pin provides external audio which may be
 15 the X.25 modified protocol of Fig. 6 encoded into audio
 tones which modulate the channel carrier on which
 information is received by the receiver ¹¹⁹~~119~~. When the
 "DIS AUDIO" pin is high, it indicates that the display
 button is pressed. The memory of the receiver 119
 stores the text to be printed by the printer. The text
 20 is downloaded through the aforementioned
 interconnection upon connection to the printer to
 generate a hard copy of the text stored in the memory.

CL Disclosure of Invention

5 The present invention provides an integration of
 an electronic mail system with an RF information
 transmission network for transmitting electronic mail
 originating at processors either within or outside an
 electronic mail system by RF communication to at least
 one destination processor within an electronic mail
 system by a RF receiver which ^{transfer} ~~relays~~ the information to
 the destination processor and method of use thereof.
 10 The RF receiver stores the received information which
 is to be ^{transferred} ~~relayed~~ to the destination processor. Storage
 in the RF receiver memory permits the reception of the
 information without a connection of the RF receiver to
 the destination processor thus eliminating the
 15 requirement that the destination processor is turned on
 and carried with the user of the destination processor.
 In a typical application with a portable PC functioning
 as the destination processor, it is important that
 reception of the information by the RF receiver does
 20 not require the drawing of power from the PC battery.
 The RF receiver automatically ^{transfers} ~~relays~~ the information to
 the destination processor upon connection of the
 RF receiver to the destination processor. The
 destination processor may be within the same electronic
 25 mail system containing the originating processor which
 originated the information or another electronic mail
 system. While a preferred application of the invention
 is with portable destination processors, it should be
 understood that the originating and destination
 30 processors may be at a fixed site or portable. The use
 of the RF receiver to receive electronic mail permits
 fixed site destination processors to receive electronic
 mail without calling the electronic mail system as in
 the prior art by using the storage of the RF receiver
 35 which may be carried on the user of the destination

processor either within an office or other site or for travel. The RF receiver provides the automatic storage of electronic mail and review of its content without interaction with the destination processor. The stored
 5 messages may be transferred at a later time automatically without manually keying the message which is an important consideration in using portable PC's. The problems of the prior art in delivering electronic mail to destination processors within an electronic
 10 mail system which are being exacerbated by the increasing portability of personal computers and the absence of a current system for delivering electronic mail between electronic mail systems are overcome by the present invention.

15 The present invention transmits electronic mail from an originating processor to at least one destination processor through an interface switch. The interface switch connects an electronic mail system and/or at least one additional processor to ^{an} RF data
 20 transmission network which transmits the information to a RF receiver which is connectable to the destination processor to ^{transfer} ~~relay~~ the received RF message from the RF receiver to the destination processor.

25 The invention is user friendly in that the minimum amount of information which must be provided to initiate the transmission of electronic mail from an originating processor to at least one destination processor is an identification of the destination processor and information indicating that the message
 30 is to be sent by the RF information transmission network. The inputting of information that the information is to be sent by the RF information transmission network may be simplified to the extent that an icon driven display associated with the
 35 originating processor, such as a mouse, may be used to

point to an icon of a radio receiver. Alternatively, an identification of the address of the interface switch through which the information is transmitted to the RF transmission network may be inputted by the operator or a machine operating the originating processor. Finally the entering of the destination processor identified in terms such as the user's name may be entered which is compared with a look up table to determine if a match exists. If a match exists, the matched identification of the destination processor supplies an address of the interface switch and an identification of an RF receiver to receive the information and ^{transfer the information} ~~relay it~~ to the destination processor. The inputting of the destination processor in terms such as the user's name to an originating processor may be used by the destination processor, gateway switch or addressed interface switch to look up an identification number of the RF receiver within the RF information transmission network which is connectable to the destination processor which is added to the information for use by the RF information transmission network. The electronic mail system or the interface switch may append the identification number of the RF receiver to receive the information which is utilized by the RF information transmission network to determine the final destination of the RF receiver to which the message is broadcast by the RF information transmission network. The appending of the identification number of the RF receiver to the information to be broadcast to the destination processor may be inputted by an operator of the originating processor, added to the information by a comparison of the identification of the destination processor to stored identifications of destination processors stored by the originating processor to which RF messages are to be broadcast by

the RF information transmission network to identify the identification number of the RF receiver in the RF information transmission network, or by a gateway switch in the electronic mail system or the interface switch between the electronic mail system and the RF information transmission network.

The intelligence for determining the identification number of the RF receiver to receive the information is less expensive and operates most efficiently when placed within the interface switch where the aforementioned matching may be produced without requiring modification of either individual originating processors within the electronic mail system or gateway switches within the electronic mail system which have additional functions for supporting other conventional aspects of electronic mail. However, the determination of an identification number of the RF receiver which ^{transfers} ~~relays~~ the information to the destination processor may be located anywhere between the originating processor and the RF information transmission network for practicing the present invention. Similarly, the appending of the address of the interface switch to which the information is transmitted by the electronic mail system for entry into the RF information transmission network for broadcast to the RF receiver for ^{transfer} ~~relaying~~ to the destination processor may be located within any one of the originating processor, gateway switch or interface switch.

An electronic mail system for transmitting information from one of a plurality of originating processors to at least one of a plurality of destination processors in accordance with the invention includes at least one gateway switch, a gateway switch storing information received from one of the at least

00453409 120639
00453409 120639
A

A

one originating processor prior to transmission of the
 information to the at least one destination processor;
 an RF information transmission network for transmitting
 stored information received from one of the at least
 5 one gateway switch by RF transmission to at least one
 destination processor; at least one interface switch,
 an interface switch connecting a gateway switch to the
 RF information transmission network and transmitting
 stored information received from one of the at least
 10 one gateway switch to the RF information transmission
 network; and wherein the information is transmitted to
 a receiving interface switch by the electronic mail
 system in response to an address of the receiving
 interface switch which has been added to the
 15 information originated by the originating processor by
 either the originating processor or gateway switch and
 the information is transmitted from the receiving
 interface switch to the RF information transmission
 network with an address of the destination processor to
 20 receive the information which has been added by either
 the originating processor, a gateway switch or the
 receiving interface switch. The destination processors
 may be transported during operation by a user. The
 receiving interface switch removes information added by
 25 the electronic mail system to the information
 originated by the originating processor from the stored
 information received from one of the at least one
 gateway switch and adds information used by the RF
 information transmission network during transmission of
 30 the information to the information originated by the
 originating processor to an RF receiver in the RF
 information transmission network which receives the
 information and ^{+transfers} ~~relays~~ the information originated by
 the originating processor to the destination processor.

A

42

The RF receiver may be detached from the destination processor during reception of the information with a memory of the RF receiver storing the information. Storage in memory permits review of the information prior to transferring the information to the destination processor by connection the RF receiver to the destination processor. The address of the destination processor is preferably an identification of a RF receiver in the RF information transmission network which receives the information and ^{transfers} ~~relays~~ it to the destination processor.

The receiving interface switch stores information which has been stored by at least one gateway switch that is received from a plurality of originating processors, assembles the information from a plurality of originating processors into a packet and transmits the packet to the RF information transmission network. The RF information transmission network comprises a switch which receives the packet from the receiving interface switch and disassembles the packet into information from the plurality of originating processors. The RF information transmission network transmits the disassembled information, including the identification number of the RF receiver, to a switch in the RF information transmission network storing a file identified by the identification number and any destination of the RF receiver in the RF information transmission network to which the information and identification number is to be transmitted by the RF information transmission network. The switch adds any destination of the RF receiver to the information and the RF information transmission network in response to any added destination transmits the information and identification number to the destination for

RF broadcast to the RF receiver for relaying to the destination processor.

5 The electronic mail system also transmits information between an originating processor and at least one destination processor through either a public switch or a private switch telephone network without transmission by the RF information transmission network. The destination processor is addressed by a different address during transmission to the destination processor when using the public or private switch telephone network than during transmission by the RF information transmission network.

10 The RF receiver is connectable to the destination processor and in response to connection of the RF receiver to the destination processor the RF receiver transfers information stored in a memory of the RF receiver received from the originating processor to the destination processor. The number of originating processors is greater than a number of interface switches. The plurality of originating processors also function as destination processors with a RF receiver coupled thereto.

25 The address of the receiving interface switch may be added to the information originated by the originating processor by a gateway switch. The address of the receiving interface switch may be added by the gateway switch by matching an identification of the destination processor such as a name of a user of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

The address of the receiving interface switch may also be added by the originating processor. The address of the receiving interface switch may be added by an inputting of the address of the receiving interface switch along with an identification of the destination processor by an operator or a machine using the originating processor or by matching an identification of the destination processor, such as the name of the user, with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

The address of the destination processor, which preferably is an identification number of a RF receiver receiving the information and ^{transferring} ~~relaying~~ the information to the destination processor, may be added to the information originated by the originating processor by an operator or a machine using the originating processor. The identification number may also be added to the information originated by the originating processor by matching an identification of the destination processor, such as a user of the destination processor, with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

The address of the destination processor may also be added to the information originated by the originating processor by the gateway switch. The identification number may be added by the gateway switch by matching an identification of the destination processor, such as a name of a user of the destination processor, with a stored identification of a

45

destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

5 The address of the destination processor may also be added to the information originated by the originating processor by the receiving interface switch. The identification number may be added by the receiving interface switch to the information
10 originated by the originating processor by matching an identification of the destination processor, such as a name of a user of a destination processor, with a stored identification of the destination processor and adding an identification number stored with the matched
15 identification of the destination processor to the information as the identification number.

CL

Brief Description of Drawings

Fig. 1 illustrates a prior art electronic mail system.

20 Fig. 2 illustrates a prior art paging system used by the present invention.

Fig. 3 illustrates a memory map of the local switch of the prior art paging system of Fig. 2.

25 Fig. 4 illustrates a memory map of a lata switch of the prior art paging system of Fig. 2.

Fig. 5 illustrates a memory map of a hub switch of the prior art paging system of Fig. 2.

Fig. 6 illustrates a message format utilized by the prior art paging system of Fig. 2.

30 Fig. 7 illustrates a prior art connection between a receiver in the paging system of Fig. 2 and a printer.

46

A
A
Fig. 8 illustrates a block diagram of ~~an~~^a ~~electronic mail~~ system in accordance with the present invention.

5 Fig. 9 illustrates a block diagram of the connection of a plurality of electronic mail systems through a plurality of interface switches to an input port of an RF information transmission network utilized by the present invention.

10 Fig. 10 illustrates a block diagram of the transmission of information originating from a plurality of electronic mail systems to ^{an} ~~a~~ RF information transmission network to a plurality of destination processors and originating processors within a plurality of electronic mail systems in
15 accordance with the present invention.

Fig. 11 illustrates possible distributed functions for performing data processing steps necessary to transmit information from an originating processor to a destination processor using RF transmission in
20 accordance with the present invention.

Fig. 12 is a block diagram of an interface switch in accordance with the present invention.

A
66303T 6045460
66303T 6045460

CL Best Mode for Carrying Out the Invention

Figs. 8-10 illustrate a block diagram of an electronic mail system 100 which has been integrated with an RF information transmission network 302 for transmitting information from an originating processor within the electronic mail system to a destination processor within the electronic mail system utilizing RF communications in accordance with the present invention. Like reference numerals identify like parts in Figs. 1-10 and 12. The integrated system 100 differs from the prior art of Figs. 1-7 in that the originating processor, which may be any of the processors within computing systems #1-#N is provided the option of transmitting electronic mail (information) to at least one destination processor which may be any processor A-N within the processing systems #1-#N by means of an RF information transmission network 302 as described below. It should be understood that the present invention is not limited to the block diagram form of Figs. 8-10 and 12. Additionally, the communications between the originating processors, gateway switches 14 and destination processors may be through either a public or private switch telephone network ³¹⁴ ~~104~~ and are not limited to any type of telephone system interconnection. The RF information transmission network 302 functions to transmit the information which originated from ^{one of} the originating ^{processors} ~~processors~~ A-N within any of the computing systems #1-#N to the destination processor A-N within any of the computing systems #1-#N by an RF transmission to an RF receiver 119. The RF receiver 119 is connected to the destination processor with the same connections as illustrated in the prior art of Fig. 7. * Upon connection, the receiver 119 relays the information from the RF receiver to the

~~* WHEN THE RF RECEIVER 119 IS CONNECTED TO THE SAFARI COMPUTER, THE CONNECTION IS POWERED BY THE SAFARI COMPUTER.~~ ¹¹⁹ ~~119~~ ⁴⁴ ~~44~~ ⁵⁻¹⁷⁻⁹¹ ~~5-17-91~~

48

destination processor. An important aspect of the present invention is that reception and review of electronic mail can be performed without connection of the RF receiver 119 to the destination processor A-N which permits the receiver to function as a mobile electronic mail receiver. As a result, the user may move from the site of the destination processor A-N either within an office or other location or during travel while receiving electronic mail which was not possible with the prior art. Furthermore, the connection of the RF receiver 119 to the destination processor automatically transfers the electronic mail stored within the memory of the RF receiver to the destination processor without manual keyboarding. A computer program for controlling the transfer of information from the receiver 119 to a SAFARI™ laptop computer of AT&T Corporation is contained within the attached Appendix at pages 1-9. This program automatically provides transfer of the stored electronic mail stored within the memory of the RF receiver 119 into the destination processor A-N where it is accessible to application programs within the destination processor. As a result, the deficiencies of the prior art in requiring substantial expense consequent from the making of telephone calls, substantial labor resultant from the lost time of persons making telephone calls and the inability to deliver electronic mail messages and the more difficult problem of delivering electronic mail messages to portable processors is overcome. Moreover, as is explained in detail below in conjunction with Fig. 11, the initiation of an information transmission from an originating processor A-N to a destination processor A-N using an RF transmission by the RF information transmission network 302 to an individual RF receiver

has many different options which are user friendly. The initiation of the transmission of information from an originating processor A-N to a destination processor A-N using ^{RF transmission by} ~~the RF transmissions~~ of the RF information transmission network 302 only requires the identification of an address of the RF receiver, which preferably is the identification number of the receiver 119 in the RF information transmission network and the designation of an address of an interface switch in the form of an address such a "TF MOBOX" which connects the electronic mail system to the RF information transmission network as described below in conjunction with Figs. 9 and 10. The initiator of an electronic mail message, in the most user friendly form of the invention, is only required to input into the originating processor A-N an identification of the destination processor A-N which typically is in the form of a name such as "John Doe". The distributed intelligence of the system implementing the present invention, which may be located in any one of the originating processors A-N, gateway switch 14 or interface switch 304 or distributed therebetween as described below with reference to Fig. 11, may be used to add the necessary address of the interface switch connecting the electronic mail system 1-N to the RF information transmission network 302 and the identification of the RF receiver 119 in the RF information transmission network from the inputting of only an identification of the destination processor A-N. The addition of the identification number of the RF receiver 119 and the address of the interface switch may be implemented by the originating processor A-N of one of the computing systems #1-#N, a gateway switch 14 or an interface switch 304 as described below with reference to Fig. 9.

Fig. 9 illustrates a block diagram of the connection between a plurality of gateway switches with mailboxes 14 in different electronic mail systems to the RF information transmission network 302. It should be understood that multiple gateway switches with mailboxes 14 from a single electronic mail system 1-N may be connected to each interface switch 304 instead of the connection of a single gateway switch with mailbox to a single interface switch as illustrated. A plurality of interface switches 304 connect information transmitted from at least one electronic mail system as illustrated in Fig. 8, ^{Fig. 8. Optionally,} but optionally, a plurality of electronic mail systems 1-N each as illustrated in Fig. 8 are connected to a data input port of the RF information transmission system ~~as illustrated in Fig. 12~~ which is preferably hub switch 116 of the prior art paging network described above with reference to Figs. 2-6. The dotted line communication paths 306 illustrate optional information transmissions in which information from a plurality of different electronic mail systems is concentrated at a single interface switch 304. The dotted line communication paths 307 illustrate connections to additional gateway switches with mailboxes 14 within electronic mail systems 1-N.

The function of the interface switches 304 is twofold. In the first place, the interface switches 304 function as a security check to determine that information transmissions originating from a gateway switch with mailbox 14 represent transmissions which should be coupled to a hub switch 116 of the RF information transmission network 302. The security check is performed by the interface switch 304 comparing the identification number of the RF receiver 119 which has been added by either an

originating processor A-N or a gateway switch with mailboxes 14 with permissible identification numbers or the interface switch performing the addition of the identification number. The interface switch 304 also
 5 removes information added by the electronic mail system 1-N to the information originated by the originating processor A-N from the stored information received from one of the gateway switches 14 and adds information used by the RF information transmission
 10 network 302 during transmission of the information originated at the originating processor to a RF receiver 119 in the RF information transmission network 302 which receives the information and ^{+ transfers} ~~relays~~ it to the destination processor A-N. Additionally, the
 15 interface switch 304 encodes data, which is required to format the display of the CRT of the destination processor for the electronic mail system to which the destination processor is connected, in the form of a character or characters which are decoded by either the
 20 RF receiver 119 or the destination processor A-N and added in decoded form back to the information which is processed by the destination processor with a format of the electronic mail system to which the destination processor A-N is connected.

25 The interface switches 304 function to store information which has been stored by at least one gateway switch 114 that is received from a plurality of originating processors, assemble the information from a plurality of originating processors into a packet
 30 preferably having the format of that described above with reference to the prior art in Fig. 6 and transmit the packet to the hub switch 116 within the RF information transmission network 302. While the invention is not limited to the transmission of the
 35 packets from the interface switch 304 to the hub

switch 116 of the RF information transmission system 302, the hub switch is the preferable node in the RF information transmission network to which communications from the gateway switches 14 should be transmitted as a consequence of it having jurisdiction over both data switches 114 and the local switches 112 in the RF information transmission network which results in lesser network overhead.

The hub switch 116 receives the packet from the receiving interface switch 304 and disassembles the packet into information from the plurality of originating processors either within a single electronic mail system such as system 1 or from a plurality of electronic mail systems, such as systems 1-N, or from outside of any electronic mail system from at least one additional processor 312 which is connected directly to interface switch 304 to originate information to be transmitted to a destination processor A-N in an electronic mail system as described below. The RF information transmission network 302 transmits the disassembled information from the hub switch 116 including the identification number of the RF receiver 119 ^{transferring} ~~relaying~~ information to the destination processor A-N to a local switch 112 storing the file 154 identified by the identification number and any destination 178 of the RF receiver in the RF information transmission network to which the information and identification number is to be transmitted by the RF information transmission network and adds any destination of the RF receiver to the information in accordance with the prior art system described above with reference to Figs. 2-6. The RF information transmission network in response to any added destination transmits the information and identification number to the destination in accordance

with the prior art system described above with reference to Figs. 2-6 for RF broadcast to the RF receiver 119 for ^{transfer}~~relaying~~ to the destination processor A-N.

5 The information is transmitted to a receiving interface switch 304 from one or more gateway switches 14 by one or more electronic mail systems 1-N in response to an address of the receiving interface switch which has been added to the information
10 originated by the originating processor by either the originating processor or gateway switch. The information is transmitted from the receiving interface switch 304 to the RF information transmission network with an address of the destination processor, such as a
15 name of a user of the destination processor A-N, to receive the information which has been added by either the originating processor A-N, a gateway switch 14 or the receiving interface switch 304.

20 Various options exist for the adding of the address of the receiving interface switch and the address of the destination processor. Preferably, the address of the receiving interface switch is a code word, such as "TF-MOBOX", which is recognized throughout the electronic mail system when appended to
25 information as directing the information to be transmitted to the interface switch 304. The address of the destination processor is preferably the identification number of the RF receiver 119 within the RF information transmission network 302. The address
30 of the receiving interface switch may be added to the information originated by the originating processor, by a gateway switch 14 or by the originating processor A-N. The address of the receiving interface switch 304 may be added to the information by matching an
35 identification of the destination processor A-N which

may be the name of the individual utilizing the processor or some other information and adds an address of an interface switch such as the aforementioned "TF-MOBOX" stored with the matched identification of the destination processor to the information as the address of the receiving interface switch. Alternatively, the originating processor may be used to add the address of the receiving interface switch 14 by an inputting of the address of the receiving interface switch (TF-MOBOX) along with an identification of the destination processor A-N (name of recipient using the processor). The originating processor A-N may also add the address of the receiving interface switch 304 by matching an identification of the destination processor (name of the user of the processor) with a stored identification of a destination processor and adding an address of the interface switch (TF-MOBOX) stored with the matched identification of the destination processor to the information as the address of the receiving interface switch. The identification number may be added to the information originated by the originating processor or, alternatively, ^{may be} ~~is~~ added by the originating processor by matching an identification of the destination processor (the name of the user of the processor) with a stored identification of a destination processor (the authorized user of the destination processor) and adding an identification number stored with the matched identification of the destination processor to the information as the identification number of the RF receiver 119. Alternatively, the aforementioned matching process may be performed by either the gateway switch 14 or the interface switch 304.

The at least one additional processor 312 originates information from outside of any electronic

55

0045409 120649
A 0002T 0055160

mail system. The processors 312 provide an address of at least one destination processor in an electronic mail system, such as the name of the user, to receive information transmitted by the RF information transmission system 302 or an identification number of the RF receiver 119 receiving information and ^{transferring} ~~relaying~~ the information to the destination processor. The interface switch 304 which receives the information from each processor 312 adds information used by the RF information transmission network 302 during transmission of the information to the RF receiver 119 receiving the information in the same manner as described above with respect to the interface switch 304.

The advantage of connecting the processors 312 directly to the interface switch 304 is that the processors 312 are only required to have a telephone modem and support programming to format information for RF transmission to a destination processor A-N within any one of one or more electronic mail systems 1-N. The processors 312 are not required to have the necessary electronic mail system software present in originating processors A-N or interconnections with an electronic mail system. As a result of the connection to the interface switch 304, information originating from the additional processors 312 may be transmitted by RF transmission to a destination processor A-N within any one or a plurality of electronic mail systems with the user of the processor 312 or the processor 312 or the interface switch 304 only having to supply an identification number of the receiver 119 to input information into the RF information transmission system 302 for RF transmission to a destination processor.

The difference between originating information by one of the additional processors 312 outside of any electronic mail system and originating information by one of the processors within one of the electronic mail systems is that the direct connection of the additional processor to the interface switch 304 eliminates the requirement for the adding of an address of the interface switch 304 which is required by the electronic mail systems to forward the information to the interface switch where necessary formatting of the information to be compatible with the RF information transmission system is performed. The interface switch 304 packetizes information originating from the additional processors 312 in the same manner as described above with respect to information originating from within an electronic mail system. Information from within an electronic mail system and originating from additional processors 312 outside of the electronic mail system may be formatted into the same packets which are forwarded to the hub switch 116. Additionally, an interface switch 304 may be connected only to the additional processors 312 to provide an interface only for processors outside of any electronic mail system to destination processors A-N within one or more electronic mail systems 1-N. The only information which is necessary to be inputted by the additional processors 312 is the address of the destination processor (user of the processor). The addition of the identification number of the receiver 119 may be added by matching of an identification of the destination processor with stored destination processors within the additional processor 312 or the interface switch 304 with an identification number of the receiver 119 ~~being~~ stored with an identification of a destination

0045409-120699
 009027-6045409

A

57

^A processor A-N ~~being~~ used as an identification of the destination processor upon a match having been made.

Fig. 11 summarizes electronic mail message entry methods for messages (information) originating from
 5 originating processors within an electronic mail system. The first entry method adds the address of the interface switch 304 and the destination processor preferably in the form of a user's name; the gateway switch 14 takes no action; and the interface switch 304
 10 adds the identification number of the RF receiver 119. The second entry method adds the address of the interface switch 304 and the identification number of the receiver 119; the gateway switch 14 takes no action; and the interface switch 304 performs only the
 15 function of verifying that the identification number which was added by the originating processor is a valid identification number within the RF information transmission network 302. In the third method, the originating processor adds the destination processor preferably in the form of the user's name; the gateway
 20 switch adds the destination of the interface switch 304; and the interface switch 304 adds the identification of the receiver 119. In the fourth method, the originating processor adds the destination processor preferably in the form of the user's name only; the gateway switch 14 adds an address of the interface switch 304 and the identification number of
 25 the receiver 119; and the interface switch takes no action other than verification that the identification number of the receiver 119 added by the gateway switch 14 is valid. In the fifth method, the operator of the originating processor adds the destination processor, points to an icon displayed on a CRT associated with the originating processor and the
 30 originating processor adds the address of the interface
 35

switch 304; the gateway switch 14 adds the identification number of the receiver 119 and the interface switch 304 takes no action other than verification. In the sixth method, the operator of the

5 the originating processor adds the destination processor, the user of the originating processor points to an icon displayed by a CRT associated with the originating processor which causes the addition of the address of the interface switch 304; the gateway switch takes no

10 action and the interface switch 304 adds the identification of the receiver 119. In the seventh method, the operator of the originating processor adds the destination processor, the user points to an icon displayed on a CRT associated with the originating

15 processor causing the addition of the address of the interface switch 304 and the receiver identification number by comparing an identification of the destination processor, such as user name of the destination processor, to an identification of

20 destination processors with identification numbers or RF receivers 119 which ^{transfer} ~~relay~~ information to the destination processor; the gateway switch 14 takes no action; and the interface switch 304 takes no action.

Fig. 12 illustrates a block diagram of an

25 interface switch 304 in accordance with the present invention. The interface switch 304 has a main CPU 400 to which is connected a floppy drive 402 and a hard drive 404 for providing memory storage for use by the CPU in executing the various functions of the interface

30 switch as described above. The program on pages ¹⁶⁻¹⁸ ~~10-14~~ of the Appendix implements the function of the interfaced switch 304 in a 3B2 computer which interfaces with the Telefind Corporation data transmission network described in the above-referenced patents and the

35 AT&T Corporation electronic mail system. A diagnostic

and maintenance port 406 is connected to the CPU in accordance with standard practice. A main bus 408 is coupled to a plurality of serial ports 410 which are connected in series with a multispeed modem 412 which is connected to one of the additional processors 312 as discussed above with reference to Fig. 9, to at least one gateway switch with mailboxes 14 in at least one electronic mail system and to a plurality of network ports which are connected to a plurality of X.25 modems 414 which are connected in series with a network port 416 which is connected to hub switch 116 of Fig. 9. A module bay controller 418 controls the bus 408 in accordance with standard practice. Alternatively, if the interface switch is not connected to a gateway switch with mailboxes 14, the interface switch functions only as a general purpose collector switch for the additional processors 312.

While the invention has been described in terms of its preferred embodiments, it should be understood that numerous modifications may be made thereto without departing from the spirit and scope as defined in the appended claims. For example, while the invention has been described in terms of utilizing a preferred RF information transmission network, it should be understood that the invention is equally applicable to other forms of RF transmission systems for broadcasting information originating from an originating processor within an electronic mail system or from an additional processor outside of any electronic mail system to a destination processor connected to an electronic mail system. It is intended that all such modifications fall within the scope of the appended claims.

CL

Appendix

5 An Appendix containing a listing of control
programs for controlling the transmission of
information between an RF receiver and a destination
processor and controlling the operation of an interface
switch in accordance with the invention is attached.
The programs are written in the C programming language.
The program for controlling the transmission of
information from the RF receiver to the destination
10 processor appears at pages 1-9 and the program for
controlling the operation of the interface switch
appears at pages 10-¹²~~14~~. The Appendix contains subject
matter which is copyrighted. A limited license is
granted to anyone who requires a copy of the program
disclosed therein for purposes of understanding or
15 analyzing the invention, but no license is granted to
make a copy for any other purposes including the
loading of a processing device with code in any form or
language.

61

663037-60155160

PAGE 62 REMOVED
"FOR CRC"

1-12/2

12 pages REMOVED

~~2.~~ ¹
~~126.~~ An originating device in accordance with claim ~~125~~

wherein:

the electronic mail originated by the programmed processor also contains an identification of the wireless device and a recipient of the electronic mail to receive the information at the one mobile processor.

³
~~127.~~ An originating device in accordance with claim ~~126~~

wherein:

the identification of the wireless device is a number.

⁴
~~128.~~ An originating device in accordance with claim ~~125~~

wherein:

the programmed processor is mobile, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the one mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one mobile processor and by the communication system.

⁵
~~129.~~ An originating device in accordance with claim ~~126~~

wherein:

the programmed processor is mobile, executes electronic mail programming to originate electronic mail which

is wirelessly transmitted from the programmed processor and by the communication system; and

the one mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one mobile processor and by the communication system.

^{6.}
~~130.~~ An originating device in accordance with claim ~~127~~³ wherein:

the programmed processor is mobile, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the one mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one mobile processor and by the communication system.

Sub 2 131. An originating device in accordance with claim 125 wherein:

the one mobile processor executes at least one application program which processes the information.

132. An originating device in accordance with claim 126 wherein:

the one mobile processor executes at least one application program which processes the information.

Sub D2
133. An originating device in accordance with claim 127 wherein:

the one mobile processor executes at least one application program which processes the information.

134. An originating device in accordance with claim 128 wherein:

B1
the one mobile processor executes at least one application program which processes the information.

135. An originating device in accordance with claim 129 wherein:

the one mobile processor executes at least one application program which processes the information.

136. An originating device in accordance with claim 130 wherein:

the one mobile processor executes at least one application program which processes the information.

13.
~~137.~~ An originating device in accordance with claim ~~125~~¹ wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail before transmission by the wireless system.

14.
~~138.~~ An originating device in accordance with claim ~~128~~⁴ wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail before transmission by the wireless system.

^{15.}
~~139~~ An originating device in accordance with claim ⁷~~131~~ wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail before transmission by the wireless system.

^{16.}
~~140~~ An originating processor in accordance with claim ¹~~125~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{17.}
~~141~~ An originating processor in accordance with claim ²~~126~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{18.}
~~142~~ An originating processor in accordance with claim ³~~127~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{19.}
~~143.~~ An originating processor in accordance with claim
⁴
~~128~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{20.}
~~144.~~ An originating processor in accordance with claim
⁵
~~129~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{21.}
~~145.~~ An originating processor in accordance with claim
⁶
~~130~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{22.}
~~146.~~ An originating processor in accordance with claim
⁷
~~131~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

23.

~~147~~. An originating processor in accordance with claim
8
~~132~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

24.

~~148~~. An originating processor in accordance with claim
9
~~133~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

25.

~~149~~. An originating processor in accordance with claim
10
~~134~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

26.

~~150~~. An originating processor in accordance with claim
11
~~135~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

27.

~~151~~. An originating processor in accordance with claim
12
~~136~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{28.}
~~152~~ An originating processor in accordance with claim
¹³
~~137~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

B/
^{29.}
~~153~~ An originating processor in accordance with claim
¹⁴
~~138~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{30.}
~~154~~ An originating processor in accordance with claim
¹⁵
~~139~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{31.}
~~155~~ An originating device in accordance with claim ¹⁶~~140~~
wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

32.

17

~~156.~~ An originating device in accordance with claim ~~141~~

wherein:

the deleted information is a header in the
electronic mail inputted by the originating device.

33.

18

~~157.~~ An originating device in accordance with claim ~~142~~

wherein:

the deleted information is a header in the
electronic mail inputted by the originating device.

34.

19

~~158.~~ An originating device in accordance with claim ~~143~~

wherein:

the deleted information is a header in the
electronic mail inputted by the originating device.

35.

1720

~~159.~~ An originating device in accordance with claim ~~144~~

wherein:

the deleted information is a header in the
electronic mail inputted by the originating device.

36.

21

~~160.~~ An originating device in accordance with claim ~~145~~

wherein:

the deleted information is a header in the
electronic mail inputted by the originating device.

37.

22

~~161.~~ An originating device in accordance with claim ~~146~~

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

38.

23

~~162.~~ An originating device in accordance with claim ~~147~~

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

39.

24

~~163.~~ An originating device in accordance with claim ~~148~~

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

40.

25

~~164.~~ An originating device in accordance with claim ~~149~~

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

41.

26

~~165.~~ An originating device in accordance with claim ~~150~~

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

42.

27

~~166.~~ An originating device in accordance with claim ~~151~~

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

⁴³
~~167~~ An originating device in accordance with claim ~~152~~²⁸

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

⁴⁴
~~168~~ An originating device in accordance with claim ~~153~~²⁹

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

⁴⁵
~~169~~ An originating device in accordance with claim ~~154~~³⁰

wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

B1
Sub 13
170. An originating device in accordance with claim 125 wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

171. An originating device in accordance with claim 126 wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

Sub 04
212. An originating device in accordance with claim 167 wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

213. An originating device in accordance with claim 168 wherein:

B
after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

214. An originating device in accordance with claim 169 wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

91.
~~215.~~ An originating device in accordance with claim ~~170~~ ⁴⁶ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

⁴⁷
~~92.~~
~~216~~ An originating device in accordance with claim ~~171~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

⁴⁸
~~93.~~
~~217~~ An originating device in accordance with claim ~~172~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

⁴⁹
~~94.~~
~~218~~ An originating device in accordance with claim ~~173~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

⁵⁰
~~95.~~
~~219~~ An originating device in accordance with claim ~~174~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

⁵¹
~~96.~~
~~220~~ An originating device in accordance with claim ~~175~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{97.}
~~221.~~ An originating device in accordance with claim ~~176~~ ⁵²
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{98.}
~~222.~~ An originating device in accordance with claim ~~177~~ ⁵³
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{99.}
~~223.~~ An originating device in accordance with claim ~~178~~ ⁵⁴
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{100.}
~~224.~~ An originating device in accordance with claim ~~179~~ ⁵⁵
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

101.
~~225.~~ An originating device in accordance with claim ~~180~~⁵⁶
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

102.
~~226.~~ An originating device in accordance with claim ~~181~~⁵⁷
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

103.
~~227.~~ An originating device in accordance with claim ~~182~~⁵⁸
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

104.
~~228.~~ An originating device in accordance with claim ~~183~~⁵⁹
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

105.
~~229.~~ An originating device in accordance with claim ~~184~~⁶⁰
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

106.

61

~~230.~~ An originating device in accordance with claim ~~185~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

101.

62

~~231.~~ An originating device in accordance with claim ~~186~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

108.

63

~~232.~~ An originating device in accordance with claim ~~187~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

109.

64

~~233.~~ An originating device in accordance with claim ~~188~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

110. ⁶⁵
~~234.~~ An originating device in accordance with claim ~~189~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

111. ⁶⁶
~~235.~~ An originating device in accordance with claim ~~190~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

112. ⁶⁷
~~236.~~ An originating device in accordance with claim ~~191~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

113. ⁶⁸
~~237.~~ An originating device in accordance with claim ~~192~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

114. ⁶⁹
~~238.~~ An originating device in accordance with claim ~~193~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

115. 70
~~239.~~ An originating device in accordance with claim ~~194~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

B/ 116. 71
~~240.~~ An originating device in accordance with claim ~~195~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

117. 72
~~241.~~ An originating device in accordance with claim ~~196~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

118. 73
~~242.~~ An originating device in accordance with claim ~~197~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

119.
~~243.~~ An originating device in accordance with claim ~~198~~ ⁷⁴
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

120.
~~244.~~ An originating device in accordance with claim ~~199~~ ⁷⁵
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

121.
~~245.~~ An originating device in accordance with claim ~~200~~ ⁷⁶
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

122.
~~246.~~ An originating device in accordance with claim ~~201~~ ⁷⁷
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

123.
~~247.~~ An originating device in accordance with claim ~~202~~ ⁷⁸
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{124.}
~~248~~ An originating device in accordance with claim ~~203~~⁷⁹
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{125.}
~~249~~ An originating device in accordance with claim ~~204~~⁸⁰
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{126.}
~~250~~ An originating device in accordance with claim ~~205~~⁸¹
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{127.}
~~251~~ An originating device in accordance with claim ~~206~~⁸²
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

128.

83

~~252.~~ An originating device in accordance with claim ~~207~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

129.

84

~~253.~~ An originating device in accordance with claim ~~208~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

130.

85

~~254.~~ An originating device in accordance with claim ~~209~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

131.

86

~~255.~~ An originating device in accordance with claim ~~210~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

132.

87

~~256.~~ An originating device in accordance with claim ~~211~~

wherein:

85

B

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{133.}
~~257.~~ An originating device in accordance with claim ~~212~~⁸⁸ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

B/
^{134.}
~~258.~~ An originating device in accordance with claim ~~213~~⁷⁹ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{135.}
~~259.~~ An originating device in accordance with claim ~~214~~⁹⁰ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

Sub D5
260. A programmed processor in accordance with claims 125-259 wherein:

the wireless system broadcasts the information and an identification of the wireless device at a location in the wireless system to the wireless device determined from

Sub B [] information stored in the wireless system pertaining to a location of the wireless device stored in the wireless system.

137.

~~261~~ An originating device in accordance with claim ~~125~~¹

wherein:

the one mobile processor is a PC and the programmed processor is a mobile PC.

138.

~~262~~ An originating device in accordance with claim ~~126~~²

wherein:

B/ the one mobile processor is a PC and the programmed processor is a mobile PC.

139.

~~263~~ An originating device in accordance with claim ~~127~~³

wherein:

the one mobile processor is a PC and the programmed processor is a mobile PC.

140.

~~264~~ An originating device in accordance with claim ~~128~~⁴

wherein:

the one mobile processor is a PC and the programmed processor is a mobile PC.

141.

~~265~~ An originating device in accordance with claim ~~129~~⁵

wherein:

the one mobile processor is a PC and the programmed processor is a mobile PC.

142.

~~266.~~ An originating device in accordance with claim ~~130~~⁶

wherein:

the one mobile processor is a PC and the
programmed processor is a mobile PC.

143.

~~267.~~ An originating device in accordance with claim ~~131~~⁷

wherein:

the one mobile processor is a PC and the
programmed processor is a mobile PC.

144.

~~268.~~ An originating device in accordance with claim ~~132~~¹³

wherein:

the one mobile processor is a PC and the
programmed processor is a mobile PC.

145.

~~269.~~ An originating device in accordance with claim ~~140~~¹⁶

wherein:

the one mobile processor is a PC and the
programmed processor is a mobile PC.

146.

~~270.~~ An originating device in accordance with claim ~~155~~³¹

wherein:

the one mobile processor is a PC and the
programmed processor is a mobile PC.

147

~~271.~~ An originating device in accordance with claim ~~170~~⁴⁶

wherein:

the one mobile processor is a PC and the
programmed processor is a mobile PC.

^{148.}
~~272.~~ An originating device in accordance with claim ⁹¹~~215~~
wherein:

the one mobile processor is a PC and the
programmed processor is a mobile PC.

^{149.}
~~273.~~ An originating device in accordance with claim ¹~~125~~
wherein:

the one mobile processor is a PC and the
programmed processor is a mobile PC; and wherein

the wireless system broadcasts the information and
an identification of the wireless device at a location in the
wireless system to the wireless device determined from
information stored in the wireless system pertaining to a
location of the wireless device in the wireless system.

B/
6095407-6095409
Sub D6
274. In a communication system comprising a wireless
system which communication system transmits electronic mail
inputted to the communication system from an originating
device which executes electronic mail programming to originate
the electronic mail, mobile processors which execute
electronic mail programming to function as a destination of
electronic mail, and a destination processor to which the
electronic mail is transmitted from the originating device and
after reception of the electronic mail by the destination
processor, information contained in the electronic mail and an

Sub 16

identification of a wireless device in the wireless system are transmitted by the wireless system to the wireless device and from the wireless device to one of the mobile processors, the wireless device and one mobile processor comprising:

a wireless receiver connected to the one mobile processor with the one mobile processor receiving the information after the identification of the wireless device is detected by the wireless receiver in a broadcast by the wireless system.

B

66907-601560

^{151.}
~~275.~~ A wireless device and mobile processor in accordance with claim ¹⁵⁰~~274~~ wherein:

the electronic mail originated by the originating device also contains an identification of the wireless device and a recipient of the electronic mail to receive the information at the one mobile processor.

^{152.}
~~276.~~ A wireless device and mobile processor in accordance with claim ¹⁵¹~~275~~ wherein:

the identification of the wireless device is a number.

^{153.}
~~277.~~ A wireless device and mobile processor in accordance with claim ¹⁵⁰~~274~~ wherein:

the originating device is a mobile processor, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the originating device and by the communication system; and

the one mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one mobile processor and by the communication system.

^{154/}
~~278.~~ A wireless device and mobile processor in accordance with claim ¹⁵¹~~275~~ wherein:

the originating device is a mobile processor, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the originating device and by the communication system; and

the one mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one mobile processor and by the communication system.

¹⁵⁵
~~279.~~ A wireless device and mobile processor in accordance with claim ¹⁵²~~276~~ wherein:

the originating device is a mobile processor, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the originating device and by the communication system; and

the one mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one mobile processor and by the communication system.

Sub D7A

280. A wireless device and mobile processor in accordance with claim 274 wherein:

the one mobile processor executes at least one application program which processes the information.

281. A wireless device and mobile processor in accordance with claim 275 wherein:

the one mobile processor executes at least one application program which processes the information.

B

282. A wireless device and mobile processor in accordance with claim 276 wherein:

the one mobile processor executes at least one application program which processes the information.

283. A wireless device and mobile processor in accordance with claim 277 wherein:

the one mobile processor executes at least one application program which processes the information.

284. A wireless device and mobile processor in accordance with claim 278 wherein:

the one mobile processor executes at least one application program which processes the information.

161.
~~285.~~ A wireless device and mobile processor in accordance with claim ~~279~~¹⁵³ wherein:

the one mobile processor executes at least one application program which processes the information.

~~162.~~
~~286.~~ A wireless device and mobile processor in accordance with claim ~~274~~¹⁵⁰ wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail.

~~163.~~
~~287.~~ A wireless device and mobile processor in accordance with claim ~~277~~¹⁵³ wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail.

~~164.~~
~~288.~~ A wireless device and mobile processor in accordance with claim ~~274~~¹⁵⁰ wherein:

after reception of the electronic mail by the destination processor, the information contained in the electronic mail is processed and transmitted in packets by the wireless system.

~~165.~~
~~289.~~ A wireless device and mobile processor in accordance with claim ~~274~~¹⁵⁰ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

¹⁴⁶
~~290~~. A wireless device and mobile processor in accordance with claim ¹⁵¹~~275~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

¹⁶⁷
~~291~~. A wireless device and mobile processor in accordance with claim ¹⁵²~~276~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

¹⁶⁸
~~292~~. A wireless device and mobile processor in accordance with claim ¹⁵³~~277~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

¹⁶⁹
~~293~~. A wireless device and mobile processor in accordance with claim ¹⁵⁴~~278~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

^{170.}
~~294.~~ A wireless device and mobile processor in
accordance with claim ¹⁵⁵~~279~~ wherein:

after reception of the electronic mail by the
destination processor, information is deleted from the
electronic mail and is not transmitted by the wireless system.

^{171.}
~~295.~~ A wireless device and mobile processor in
accordance with claim ¹⁵⁶~~280~~ wherein:

after reception of the electronic mail by the
destination processor, information is deleted from the
electronic mail and is not transmitted by the wireless system.

^{172.}
~~296.~~ A wireless device and mobile processor in
accordance with claim ¹⁵⁷~~281~~ wherein:

after reception of the electronic mail by the
destination processor, information is deleted from the
electronic mail and is not transmitted by the wireless system.

^{173.}
~~297.~~ A wireless device and mobile processor in
accordance with claim ¹⁵⁸~~282~~ wherein:

after reception of the electronic mail by the
destination processor, information is deleted from the
electronic mail and is not transmitted by the wireless system.

^{174.}
~~298.~~ A wireless device and mobile processor in
accordance with claim ¹⁵⁹~~283~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

175.

~~299.~~ A wireless device and mobile processor in accordance with claim ~~284~~¹⁶⁰ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

176.

~~300.~~ A wireless device and mobile processor in accordance with claim ~~285~~¹⁴¹ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

177.

~~301.~~ A wireless device and mobile processor in accordance with claim ~~286~~¹⁶² wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

178.

~~302.~~ A wireless device and mobile processor in accordance with claim ~~287~~¹⁶³ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

179.
~~303.~~ A wireless device and mobile processor in
accordance with claim ~~288~~¹⁶⁴ wherein:
after reception of the electronic mail by the
destination processor, information is deleted from the
electronic mail and is not transmitted by the wireless system.

180.
~~304.~~ A wireless device and mobile processor in
accordance with claim ~~289~~¹⁶⁵ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

B
181.
~~305.~~ A wireless device and mobile processor in accordance
with claim ~~290~~¹⁶⁶ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

182.
~~306.~~ A wireless device and mobile processor in
accordance with claim ~~291~~¹⁶⁷ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

183.
~~307.~~ A wireless device and mobile processor in
accordance with claim ~~292~~¹⁶⁸ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

184.
~~308.~~ A wireless device and mobile processor in
accordance with claim ~~293~~¹⁶⁹ wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

185.

~~309~~ A wireless device and mobile processor in accordance with claim ~~294~~¹⁷⁰ wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

186.

~~310~~ A wireless device and mobile processor in accordance with claim ~~295~~¹⁷¹ wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

187.

~~311~~ A wireless device and mobile processor in accordance with claim ~~296~~¹⁷² wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

188.

~~312~~ A wireless device and mobile processor in accordance with claim ~~297~~¹⁷³ wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

189.

~~313~~ A wireless device and mobile processor in accordance with claim ~~298~~¹⁷⁴ wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

190.
~~314~~ A wireless device and mobile processor in
accordance with claim ~~299~~¹⁷⁵ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

191.
~~315~~ A wireless device and mobile processor in
accordance with claim ~~300~~¹⁷⁶ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

192.
~~316~~ A wireless device and mobile processor in
accordance with claim ~~301~~¹⁷⁷ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

193.
~~317~~ A wireless device and mobile processor in
accordance with claim ~~302~~¹⁷⁸ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

194.
~~318~~ A wireless device and mobile processor in
accordance with claim ~~303~~¹⁷⁹ wherein:
the deleted information is a header in the
electronic mail inputted by the originating device.

319. A wireless device and mobile processor in
accordance with claim ~~274~~ wherein:

364. A wireless device and mobile processor in accordance with claim 318 wherein:

after reception by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

241.
~~365~~ A wireless device and mobile processor in accordance with claim ¹⁹⁵~~319~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

242.
~~366~~ A wireless device and mobile processor in accordance with claim ¹⁹⁶~~320~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

243.
~~367~~ A wireless device and mobile processor in accordance with claim ¹⁹⁷~~321~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

244.
~~368~~ A wireless device and mobile processor in accordance with claim ¹⁹⁸~~322~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

245.

~~369~~ A wireless device and mobile processor in accordance with claim ~~323~~¹⁹⁹ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

246.

~~370~~ A wireless device and mobile processor in accordance with claim ~~324~~²⁰⁰ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

247.

~~371~~ A wireless device and mobile processor in accordance with claim ~~325~~²⁰¹ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

248.

~~372~~ A wireless device and mobile processor in accordance with claim ~~326~~²⁰² wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

249.
~~373~~ A wireless device and mobile processor in
accordance with claim ~~327~~²⁰³ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

250.
~~374~~ A wireless device and mobile processor in
accordance with claim ~~328~~²⁰⁴ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

251.
~~375~~ A wireless device and mobile processor in
accordance with claim ~~329~~²⁰⁵ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

252.
~~376~~ A wireless device and mobile processor in
accordance with claim ~~330~~²⁰⁶ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

253.
~~377~~ A wireless device and mobile processor in
accordance with claim ~~331~~²⁰⁷ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{254.}
~~378.~~ A wireless device and mobile processor in accordance with claim ²⁰⁸~~332~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

B
^{255.}
~~379.~~ A wireless device and mobile processor in accordance with claim ²⁰⁹~~333~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{256.}
~~380.~~ A wireless device and mobile processor in accordance with claim ²¹⁰~~334~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{257.}
~~381.~~ A wireless device and mobile processor in accordance with claim ²¹¹~~335~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

258.

~~382~~. A wireless device and mobile processor in
accordance with claim ~~336~~²¹² wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

259.

~~383~~. A wireless device and mobile processor in
accordance with claim ~~337~~²¹³ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

260.

~~384~~. A wireless device and mobile processor in
accordance with claim ~~338~~²¹⁴ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

261.

~~385~~. A wireless device and mobile processor in
accordance with claim ~~339~~²¹⁵ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

262.

~~386~~. A wireless device and mobile processor in
accordance with claim ~~340~~²¹⁶ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

~~387.~~ ^{263.} A wireless device and mobile processor in accordance with claim ~~341~~ ³¹⁷ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

~~388.~~ ^{264.} A wireless device and mobile processor in accordance with claim ~~342~~ ³¹⁸ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

~~389.~~ ^{265.} A wireless device and mobile processor in accordance with claim ~~343~~ ³¹⁹ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

~~390.~~ ^{266.} A wireless device and mobile processor in accordance with claim ~~344~~ ³²⁰ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

267.

~~391.~~ A wireless device and mobile processor in
accordance with claim ~~345~~²²¹ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

268.

~~392.~~ A wireless device and mobile processor in
accordance with claim ~~346~~²²² wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

269.

~~393.~~ A wireless device and mobile processor in
accordance with claim ~~347~~²²³ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

270.

~~394.~~ A wireless device and mobile processor in
accordance with claim ~~348~~²²⁴ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

271.

~~395.~~ A wireless device and mobile processor in
accordance with claim ~~349~~²²⁵ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{272.}
~~396.~~ A wireless device and mobile processor in accordance with claim ²²⁴~~350~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

BA
^{273.}
~~397.~~ A wireless device and mobile processor in accordance with claim ²²⁷~~351~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{274.}
~~398.~~ A wireless device and mobile processor in accordance with claim ²²⁸~~352~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{275.}
~~399.~~ A wireless device and mobile processor in accordance with claim ²²⁹~~353~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

276.

~~400.~~ A wireless device and mobile processor in
accordance with claim ~~354~~²³⁰ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

277.

~~401.~~ A wireless device and mobile processor in
accordance with claim ~~355~~²³¹ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

278.

~~402.~~ A wireless device and mobile processor in
accordance with claim ~~356~~²³² wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

279.

~~403.~~ A wireless device and mobile processor in
accordance with claim ~~357~~²³³ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

280.

~~404.~~ A wireless device and mobile processor in
accordance with claim ~~358~~²³⁴ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

281.
~~405.~~ A wireless device and mobile processor in accordance with claim ~~359~~²³⁵ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

282.
~~406.~~ A wireless device and mobile processor in accordance with claim ~~360~~²³⁶ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

283.
~~407.~~ A wireless device and mobile processor in accordance with claim ~~361~~²³⁷ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

284.
~~408.~~ A wireless device and mobile processor in accordance with claim ~~362~~²³⁸ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

~~285.~~
~~409.~~ A wireless device and mobile processor in
accordance with claim ~~363~~²³⁹ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

~~286.~~
~~410.~~ A wireless device and mobile processor in
accordance with claim ~~364~~²⁴⁰ wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

B1
Sub 99
411. A wireless device and mobile processor in
accordance with claims 274-410 wherein:

the wireless system broadcasts the information and
an identification of the wireless device at a location in the
wireless system to the wireless device determined from
information stored in the wireless system pertaining to a
location of the wireless device in the wireless system.

~~288.~~
~~412.~~ A wireless device and mobile processor in
accordance with claim ~~274~~¹⁵⁰ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

~~289.~~
~~413.~~ A wireless device and mobile processor in
accordance with claim ~~275~~¹⁵¹ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

290.

~~414.~~ A wireless device and mobile processor in
accordance with claim ¹⁵²~~276~~ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

291.

~~415.~~ A wireless device and mobile processor in
accordance with claim ¹⁵³~~277~~ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

292.

~~416.~~ A wireless device and mobile processor in
accordance with claim ¹⁵⁴~~278~~ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

293.

~~417.~~ A wireless device and mobile processor in
accordance with claim ¹⁵⁵~~279~~ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

294.

~~418.~~ A wireless device and mobile processor in
accordance with claim ¹⁵⁶~~280~~ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

295.

~~419.~~ A wireless device and mobile processor in
accordance with claim ~~286~~¹⁶² wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

296.

~~420.~~ A wireless device and mobile processor in
accordance with claim ~~289~~¹⁶⁵ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

297.

~~421.~~ A wireless device and mobile processor in
accordance with claim ~~304~~¹⁸⁰ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

298.

~~422.~~ A wireless device and mobile processor in
accordance with claim ~~320~~¹⁹⁶ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

299.

~~423.~~ A wireless device and mobile processor in
accordance with claim ~~365~~²⁴¹ wherein:

the one mobile processor is a PC and the
originating device is a mobile PC.

300 ~~320~~

~~424.~~ A wireless device and mobile processor in
accordance with claim ~~274~~¹⁵⁰ wherein:

the one mobile processor is a PC and the originating device is a mobile PC; and

the wireless system broadcasts the information and an identification of the wireless device at a location in the wireless system to the wireless device determined from information stored in the wireless system pertaining to a location of the wireless device stored in the wireless system.

425. A communication system comprising:

mobile devices, each mobile device comprising a wireless device connected to a mobile processor which executes electronic mail programming to function as a destination of electronic mail, the wireless device after receiving a broadcast of information and an identification of the wireless device transmits the information to the connected mobile processor;

a wireless system which transmits the information and the identification of the wireless device and broadcasts the information and the identification of the wireless device;

a programmed processor which executes electronic mail programming to originate the electronic mail which contains an address of a destination to which the electronic mail is transmitted and the information; and

a destination processor which receives the electronic mail and is the destination of the electronic mail; and wherein

after reception of the electronic mail by the destination processor, the information and the identification

Sub D10
of the wireless device are transmitted to the wireless system and broadcast to the wireless device.

~~302,~~ 301
~~426.~~ A communication system in accordance with claim ~~425~~
wherein:

the electronic mail originated by the programmed processor also contains an identification of the wireless device and a recipient of the electronic mail to receive the information at the connected mobile processor.

B/ 6095409-100600
~~303.~~ 301
~~427.~~ A communication system in accordance with claim ~~425~~
wherein:

the identification of the wireless device is a number.

~~304,~~ 301
~~428.~~ A communication system in accordance with claim ~~425~~
wherein:

the programmed processor is mobile, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the connected mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the connected mobile processor and by the communication system.

~~305.~~ 302
~~429.~~ A communication system in accordance with claim ~~426~~
wherein:

the programmed processor is mobile, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the connected mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the connected mobile processor and by the communication system.

306.
~~430.~~ A communication system in accordance with claim ~~427~~ *303*
wherein:

the programmed processor is mobile, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the connected mobile processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the connected mobile processor and by the communication system.

431. A communication system in accordance with claim 425
wherein:

the connected mobile processor executes at least one application program which processes the information.

432. A communication system in accordance with claim 426
wherein:

Sub D11

the connected mobile processor executes at least one application program which processes the information.

433. A communication system in accordance with claim 427 wherein:

the connected mobile processor executes at least one application program which processes the information.

B

434. A communication system in accordance with claim 428 wherein:

the connected mobile processor executes at least one application program which processes the information.

435. A communication system in accordance with claim 429 wherein:

the connected mobile processor executes at least one application program which processes the information.

436. A communication system in accordance with claim 430 wherein:

the connected mobile processor executes at least one application program which processes the information.

313.

~~437.~~ A communication system in accordance with claim ~~425~~ ³⁰¹ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

314.

~~438~~ A communication system in accordance with claim ~~426~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

315.

~~439~~ A communication system in accordance with claim ~~427~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

316.

~~440~~ A communication system in accordance with claim ~~428~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

317.

~~441~~ A communication system in accordance with claim ~~429~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

318.

~~442~~ A communication system in accordance with claim ~~430~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

319.

307

~~443.~~ A communication system in accordance with claim ~~431~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

320.

308

~~444.~~ A communication system in accordance with claim ~~432~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

321.

309

~~445.~~ A communication system in accordance with claim ~~433~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

322.

310

~~446.~~ A communication system in accordance with claim ~~434~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

323.

311

~~447.~~ A communication system in accordance with claim ~~435~~
wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

324.

312

~~448.~~ A communication system in accordance with claim ~~436~~
wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

325.

313

~~449.~~ A communication system in accordance with claim ~~437~~
wherein:

the deleted information is a header in the electronic mail originated by the programmed processor.

326.

314

~~450.~~ A communication system in accordance with claim ~~438~~
wherein:

the deleted information is a header in the electronic mail originated by the programmed processor.

327.

315

~~451.~~ A communication system in accordance with claim ~~439~~
wherein:

the deleted information is a header in the electronic mail originated by the programmed processor.

~~328.~~

~~452.~~ A communication system in accordance with claim ~~440~~ ³¹⁶ ~~322~~

wherein:

the deleted information is a header in the
electronic mail originated by the programmed processor.

~~329.~~

~~453.~~ A communication system in accordance with claim ~~441~~ ³¹⁷ ~~323~~

wherein:

the deleted information is a header in the
electronic mail originated by the programmed processor.

~~330.~~

~~454.~~ A communication system in accordance with claim ~~442~~ ³¹⁸ ~~324~~

wherein:

the deleted information is a header in the
electronic mail originated by the programmed processor.

~~331.~~

~~455.~~ A communication system in accordance with claim ~~443~~ ³¹⁹ ~~325~~

wherein:

the deleted information is a header in the
electronic mail originated by the programmed processor.

~~332.~~

~~456.~~ A communication system in accordance with claim ~~444~~ ³²⁰ ~~326~~

wherein:

the deleted information is a header in the
electronic mail originated by the programmed processor.

~~333.~~

~~457.~~ A communication system in accordance with claim ~~445~~ ³²¹ ~~327~~

wherein:

120

1

the deleted information is a header in the
electronic mail originated by the programmed processor.

³³⁴
~~458~~. A communication system in accordance with claim ~~446~~ ³²²
wherein:

the deleted information is a header in the
electronic mail originated by the programmed processor.

³³⁵
~~459~~. A communication system in accordance with claim ~~447~~ ³²³
wherein:

the deleted information is a header in the
electronic mail originated by the programmed processor.

³³⁶
~~460~~. A communication system in accordance with claim ~~448~~ ³²⁴
wherein:

the deleted information is a header in the
electronic mail originated by the programmed processor.

461. A communication system in accordance with claim 425
wherein:

after reception of the electronic mail by the
destination processor, a check is performed to determine if
the information should be transmitted by the wireless system
to the wireless device.

462. A communication system in accordance with claim 426
wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

495. A communication system in accordance with claim 459 wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

496. A communication system in accordance with claim 460 wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

313.

337

~~497.~~ A communication system in accordance with claim ~~461~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

374.

338

~~498.~~ A communication system in accordance with claim ~~462~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

375.

339

~~499.~~ A communication system in accordance with claim ~~463~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

376.

340

~~500.~~ A communication system in accordance with claim ~~464~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

377.

341

~~501.~~ A communication system in accordance with claim ~~465~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

378.

342

~~502.~~ A communication system in accordance with claim ~~466~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

379.

343

~~503.~~ A communication system in accordance with claim ~~467~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

380.

344

~~504.~~ A communication system in accordance with claim ~~468~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

381.

345

~~505.~~ A communication system in accordance with claim ~~469~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

382.

346

~~506.~~ A communication system in accordance with claim ~~470~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

383.

347

~~507.~~ A communication system in accordance with claim ~~471~~
wherein:

379.

343

~~503.~~ A communication system in accordance with claim ~~467~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

380.

344

~~504.~~ A communication system in accordance with claim ~~468~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

381.

345

~~505.~~ A communication system in accordance with claim ~~469~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

382.

346

~~506.~~ A communication system in accordance with claim ~~470~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

383.

347

~~507.~~ A communication system in accordance with claim ~~471~~

wherein:

124

3

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

384. ³⁴⁸
~~508.~~ A communication system in accordance with claim ~~472~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

B **385.** ³⁴⁹
~~509.~~ A communication system in accordance with claim ~~473~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

386. ³⁵⁰
~~510.~~ A communication system in accordance with claim ~~474~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

387. ³⁵¹
~~511.~~ A communication system in accordance with claim ~~475~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

388.

352

~~512.~~ A communication system in accordance with claim ~~476~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

389.

353

~~513.~~ A communication system in accordance with claim ~~477~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

390.

354

~~514.~~ A communication system in accordance with claim ~~478~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

391.

355

~~515.~~ A communication system in accordance with claim ~~479~~
wherein:

the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

392

356

~~516.~~ A communication system in accordance with claim ~~480~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

393.

357

~~517~~. A communication system in accordance with claim ~~481~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

394.

358

~~518~~. A communication system in accordance with claim ~~482~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

395.

359

~~519~~. A communication system in accordance with claim ~~483~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

396

360

~~520~~. A communication system in accordance with claim ~~484~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

127

2

397.

361

~~521.~~ A communication system in accordance with claim ~~485~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

398.

362

~~522.~~ A communication system in accordance with claim ~~486~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

399.

363

~~523.~~ A communication system in accordance with claim ~~487~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

400.

364

~~524.~~ A communication system in accordance with claim ~~488~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

401.

365

~~525.~~ A communication system in accordance with claim ~~489~~

wherein:

128

B

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{402.}
~~526.~~ A communication system in accordance with claim ³⁶⁶~~490~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{403.}
~~527.~~ A communication system in accordance with claim ³⁶⁷~~491~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{404.}
~~528.~~ A communication system in accordance with claim ³⁶⁸~~492~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{405.}
~~529.~~ A communication system in accordance with claim ³⁶⁹~~493~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

406.

370

~~530.~~ A communication system in accordance with claim ~~494~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

407.

371

~~531.~~ A communication system in accordance with claim ~~495~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

408.

372

~~532.~~ A communication system in accordance with claim ~~496~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

533. A communication system in accordance with claims 425-532 wherein:

the wireless system broadcasts the information and the identification of the wireless device at a location in the wireless system to the wireless device determined from information stored in the wireless system pertaining to a location of the wireless device stored in the wireless system.

410.

301

~~534.~~ A communication system in accordance with claim ~~425~~

wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

^{411.}
~~535.~~ A communication system in accordance with claim ³⁰²~~426~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

^{412.}
~~536.~~ A communication system in accordance with claim ³⁰³~~427~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

^{413.}
~~537.~~ A communication system in accordance with claim ³⁰⁴~~428~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

^{414.}
~~538.~~ A communication system in accordance with claim ³⁰⁵~~429~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

^{415.}
~~539.~~ A communication system in accordance with claim ³⁰⁶~~430~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

416. 307
~~540.~~ A communication system in accordance with claim ~~431~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

417. 313
~~541.~~ A communication system in accordance with claim ~~437~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

418. 325
~~542.~~ A communication system in accordance with claim ~~449~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

419. 337
~~543.~~ A communication system in accordance with claim ~~461~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

420. 373
~~544.~~ A communication system in accordance with claim ~~497~~
wherein:

the connected mobile processor is a PC and the
programmed processor is a mobile PC.

545. A communication system in accordance with claim 425
wherein:

423.

422

~~547.~~ The mobile processor in accordance with claim ~~546~~

wherein:

the electronic mail originated by the programmed processor also contains an identification of the wireless device and a recipient of the electronic mail to receive the information.

424.

422

~~548.~~ The mobile processor in accordance with claim ~~546~~

wherein:

the identification of the wireless device is a number.

425.

423

~~549.~~ The mobile processor in accordance with claim ~~547~~

wherein:

the identification of the wireless device is a number.

550. The mobile processor in accordance with claim 546

wherein:

the programmed processor executes at least one application program which processes the information.

551. The mobile processor in accordance with claim 547

wherein:

the programmed processor executes at least one application program which processes the information.

Sub 015/
552. The mobile processor in accordance with claim 548 wherein:

the programmed processor executes at least one application program which processes the information.

553. The mobile processor in accordance with claim 549 wherein:

the programmed processor executes at least one application program which processes the information.

B
430.

554. The mobile processor in accordance with claim 546 wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail.

431.

555. The mobile processor in accordance with claim 550 wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail.

432.

556. The mobile processor in accordance with claim 546 wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

433.

423

~~557~~ The mobile processor in accordance with claim ~~547~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

434.

424

~~558~~ The mobile processor in accordance with claim ~~548~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

435.

425

~~559~~ The mobile processor in accordance with claim ~~549~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

436.

426

~~560~~ The mobile processor in accordance with claim ~~550~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

437.

~~561.~~ The mobile processor in accordance with claim ~~551~~ ⁴²⁷

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

438.

~~562.~~ The mobile processor in accordance with claim ~~552~~ ⁴²⁸

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

439.

~~563.~~ The mobile processor in accordance with claim ~~553~~ ⁴²⁹

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

440.

~~564.~~ The mobile processor in accordance with claim ~~554~~ ⁴³⁰

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

441.

~~565.~~ The mobile processor in accordance with claim ~~555~~ ⁴³¹

wherein:

136

B

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

442.
~~566.~~ The mobile processor in accordance with claim ~~556~~ ⁴³²
wherein:

the deleted information is a header in the electronic mail.

443.
~~567.~~ The mobile processor in accordance with claim ~~557~~ ⁴³³
wherein:

the deleted information is a header in the electronic mail.

444.
~~568.~~ The mobile processor in accordance with claim ~~558~~ ⁴³⁴
wherein:

the deleted information is a header in the electronic mail.

445.
~~569.~~ The mobile processor in accordance with claim ~~559~~ ⁴³⁵
wherein:

the deleted information is a header in the electronic mail.

446.
~~570.~~ The mobile processor in accordance with claim ~~560~~ ⁴³⁶
wherein:

the deleted information is a header in the electronic mail.

447.

~~571~~. The mobile processor in accordance with claim ~~561~~ ⁴³⁷

wherein:

the deleted information is a header in the
electronic mail.

448.

~~572~~. The mobile processor in accordance with claim ~~562~~ ⁴³⁸

wherein:

the deleted information is a header in the
electronic mail.

449.

~~573~~. The mobile processor in accordance with claim ~~563~~ ⁴³⁹

wherein:

the deleted information is a header in the
electronic mail.

450.

~~574~~. The mobile processor in accordance with claim ~~564~~ ⁴⁴⁰

wherein:

the deleted information is a header in the
electronic mail.

451.

~~575~~. The mobile processor in accordance with claim ~~565~~ ⁴⁴¹

wherein:

the deleted information is a header in the
electronic mail.

576. The mobile processor in accordance with claim 546

wherein:

Sub D16
after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

605. The mobile processor in accordance with claim 575 wherein:

B
after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

482. 452
~~606~~ The mobile processor in accordance with claim ~~576~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

483. 453
~~607~~ The mobile processor in accordance with claim ~~577~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

484. 454
~~608~~ The mobile processor in accordance with claim ~~578~~
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{485.}
~~609.~~ The mobile processor in accordance with claim ~~579~~ ⁴⁵⁵
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

B
^{486.}
~~610.~~ The mobile processor in accordance with claim ~~580~~ ⁴⁵⁶
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{487.}
~~611.~~ The mobile processor in accordance with claim ~~581~~ ⁴⁵⁷
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{488.}
~~612.~~ The mobile processor in accordance with claim ~~582~~ ⁴⁵⁸
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

489.

~~613~~. The mobile processor in accordance with claim ~~583~~

459

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

490.

~~614~~. The mobile processor in accordance with claim ~~584~~

460

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

491.

~~615~~. The mobile processor in accordance with claim ~~585~~

461

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

492.

~~616~~. The mobile processor in accordance with claim ~~586~~

462

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

493.

~~617~~. The mobile processor in accordance with claim ~~587~~

463

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{494.}
~~618.~~ The mobile processor in accordance with claim ~~588~~⁴⁶⁴
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{495.}
~~619.~~ The mobile processor in accordance with claim ~~589~~⁴⁶⁵
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{496.}
~~620.~~ The mobile processor in accordance with claim ~~590~~⁴⁶⁶
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

^{497.}
~~621.~~ The mobile processor in accordance with claim ~~591~~⁴⁶⁷
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

498.

~~622.~~ The mobile processor in accordance with claim ~~592~~ ⁴⁶⁸

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

499

~~623.~~ The mobile processor in accordance with claim ~~593~~ ⁴⁶⁹

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

500.

~~624.~~ The mobile processor in accordance with claim ~~594~~ ⁴⁷⁰

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

501.

~~625.~~ The mobile processor in accordance with claim ~~595~~ ⁴⁷¹

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

502.

~~626.~~ The mobile processor in accordance with claim ~~596~~ ⁴⁷²

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

503.

473

~~627~~. The mobile processor in accordance with claim ~~527~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

504.

474

~~628~~. The mobile processor in accordance with claim ~~528~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

505

475

~~629~~. The mobile processor in accordance with claim ~~529~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

506

476

~~630~~. The mobile processor in accordance with claim ~~600~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

507.

~~631~~ The mobile processor in accordance with claim ~~601~~⁴⁷⁷

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

508.

~~632~~ The mobile processor in accordance with claim ~~602~~⁴⁷⁸

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

509.

~~633~~ The mobile processor in accordance with claim ~~603~~⁴⁷⁹

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

510.

~~634~~ The mobile processor in accordance with claim ~~604~~⁴⁸⁰

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

511.

~~635~~ The mobile processors in accordance with claim ~~605~~⁴⁸¹

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

636. The mobile processor in accordance with claims 546-635 wherein:

the wireless system broadcasts the information and the identification of the wireless device at a location in the wireless system determined from information stored in the wireless system pertaining to a location of the wireless device in the wireless system.

637. A mobile processor for use in a communication system including a wireless system which transmits and receives wireless communications including electronic mail transmitted to and received by mobile processors, wherein each of the mobile processors executes electronic mail programming to function as an originator or destination of electronic mail, the mobile processor comprising:

a programmed processor which executes electronic mail programming to wirelessly transmit electronic mail to the communication system and wirelessly receive electronic mail from the communication system; and wherein

when the programmed processor sends electronic mail to the communication system containing an address of a destination processor included in the communication system and information, the destination processor receives the information, and after receiving the information, an

Sub 17

identification of a wireless device functioning as a wireless destination of the information and the information are transmitted by the wireless system and broadcast to the wireless device which receives the information and transmits the information to one of the mobile processors connected thereto.

514.
~~638.~~ A mobile processor in accordance with claim ~~637~~ *513*
wherein:

87

the electronic mail originated by the programmed processor also contains an identification of the wireless device and a recipient of the electronic mail to receive the information.

515.
~~639.~~ A mobile processor in accordance with claim ~~637~~ *513*
wherein:

the identification of the wireless device is a number.

516.
~~640.~~ A mobile processor in accordance with claim ~~638~~ *514*
wherein:

the identification of the wireless device is a number.

Sub 18

641. A mobile processor in accordance with claim 637
wherein:

the programmed processor executes at least one application program which processes the information.

Sub 18

642. A mobile processor in accordance with claim 638 wherein:

the programmed processor executes at least one application program which processes the information.

643. A mobile processor in accordance with claim 639 wherein:

the programmed processor executes at least one application program which processes the information.

644. A mobile processor in accordance with claim 640 wherein:

the programmed processor executes at least one application program which processes the information.

521.
~~645.~~ A mobile processor in accordance with claim ~~637~~ *513* wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail.

522.
~~646.~~ A mobile processor in accordance with claim ~~637~~ *513* wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

523.

514

~~647~~. A mobile processor in accordance with claim ~~638~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

524.

515

~~648~~. A mobile processor in accordance with claim ~~639~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

525.

516

~~649~~. A mobile processor in accordance with claim ~~640~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

526.

517

~~650~~. A mobile processor in accordance with claim ~~641~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

527.

518

~~651~~. A mobile processor in accordance with claim ~~642~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

528.

519

~~652~~. A mobile processor in accordance with claim ~~643~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

529.

520

~~653~~. A mobile processor in accordance with claim ~~644~~

wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

530.

521

~~654~~. A mobile processor in accordance with claim ~~646~~

wherein:

the deleted information is a header in the electronic mail transmitted by the programmed processor.

531.

522

~~655~~. A mobile processor in accordance with claim ~~647~~

wherein:

the deleted information is a header in the electronic mail transmitted by the programmed processor.

532.

523

~~656~~. A mobile processor in accordance with claim ~~648~~

wherein:

the deleted information is a header in the
electronic mail transmitted by the programmed processor.

533.

~~657~~. A mobile processor in accordance with claim ~~649~~⁵²⁵
wherein:

the deleted information is a header in the
electronic mail transmitted by the programmed processor.

534.

~~658~~. A mobile processor in accordance with claim ~~650~~⁵²⁶
wherein:

the deleted information is a header in the
electronic mail transmitted by the programmed processor.

535.

~~659~~. A mobile processor in accordance with claim ~~651~~⁵²⁷
wherein:

the deleted information is a header in the
electronic mail transmitted by the programmed processor.

536.

~~660~~. A mobile processor in accordance with claim ~~652~~⁵²⁸
wherein:

the deleted information is a header in the
electronic mail transmitted by the programmed processor.

537.

~~661~~. A mobile processor in accordance with claim ~~653~~⁵²⁹
wherein:

the deleted information is a header in the
electronic mail transmitted by the programmed processor.

Sub D19
686. A mobile processor in accordance with claim 661 wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

563. ~~687.~~ A mobile processor in accordance with claim ~~662~~ ⁵³⁸ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

564. ~~688.~~ A mobile processor in accordance with claim ~~663~~ ⁵³⁹ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

565. ~~689.~~ A mobile processor in accordance with claim ~~664~~ ⁵⁴⁰ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

566. ~~690.~~ A mobile processor in accordance with claim ~~665~~ ⁵⁴¹ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

547.

~~691~~. A mobile processor in accordance with claim ~~666~~⁵⁴² wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

548.

~~692~~. A mobile processor in accordance with claim ~~667~~⁵⁴³ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

549.

~~693~~. A mobile processor in accordance with claim ~~668~~⁵⁴⁴ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

570.

~~694~~. A mobile processor in accordance with claim ~~669~~⁵⁴⁵ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

571.

~~695~~. A mobile processor in accordance with claim ~~670~~ ⁵⁴⁰

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

572.

~~696~~. A mobile processor in accordance with claim ~~671~~ ⁵⁴⁷

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

573.

~~697~~. A mobile processor in accordance with claim ~~672~~ ⁵⁴⁸

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

574.

~~698~~. A mobile processor in accordance with claim ~~673~~ ⁵⁴⁹

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

575.

~~699~~. A mobile processor in accordance with claim ~~674~~ ⁵⁵⁰

wherein:

154

B

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

576.

551

~~700.~~ A mobile processor in accordance with claim ~~675~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

577

552

~~701.~~ A mobile processor in accordance with claim ~~676~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

578.

553

~~702.~~ A mobile processor in accordance with claim ~~677~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

579.

554

~~703.~~ A mobile processor in accordance with claim ~~678~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

15

B

580.

555

~~704.~~ A mobile processor in accordance with claim ~~679~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

581.

556

~~705.~~ A mobile processor in accordance with claim ~~680~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

582.

557

~~706.~~ A mobile processor in accordance with claim ~~681~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

583.

558

~~707.~~ A mobile processor in accordance with claim ~~682~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

584.

559

~~708.~~ A mobile processor in accordance with claim ~~683~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

⁵⁸⁵
~~709~~. A mobile processor in accordance with claim ~~684~~ ⁵⁶⁰
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

B ⁵⁸⁶
~~710~~. A mobile processor in accordance with claim ~~685~~ ⁵⁴¹
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

⁵⁸⁷
~~711~~. A mobile processor in accordance with claim ~~686~~ ⁵⁶²
wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

Sub D124
712. A mobile processor in accordance with claims 637-711 wherein:

the wireless system broadcasts the information and the identification of the wireless device at a location in the wireless system determined from information stored in the

Sub 020
wireless system pertaining to a location of the wireless device in the wireless system.

B
713. In a communication system comprising a wireless system which communication system transmits electronic mail inputted to the communication system from an originating device, processors which execute electronic mail programming to function as a destination of electronic mail, and a destination processor to which the electronic mail is transmitted from the originating device and after reception of the electronic mail by the destination processor, information contained in the electronic mail and an identification of a wireless device in the wireless system are transmitted by the wireless system to the wireless device and from the wireless device to one of the processors connected thereto, the originating device comprising:

a programmed processor which executes electronic mail programming to originate the electronic mail, the electronic mail containing an address of the destination processor and the information which is transmitted to the destination processor.

590.

714. An originating device in accordance with claim 713 wherein:

the electronic mail originated by the programmed processor also contains an identification of the wireless device and a recipient of the electronic mail to receive the information at the one mobile processor.

591.

589

~~715~~. An originating device in accordance with claim ~~713~~

wherein:

the identification of the wireless device is a number.

592.

590

~~716~~. An originating device in accordance with claim ~~714~~

wherein:

the identification of the wireless device is a number.

593.

589

~~717~~. An originating device in accordance with claim ~~713~~

wherein:

the programmed processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the one processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one processor and by the communication system.

594.

590

~~718~~. An originating device in accordance with claim ~~714~~

wherein:

the programmed processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

159

B

the one processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one processor and by the communication system.

595.

591

~~719~~. An originating device in accordance with claim ~~715~~, wherein:

the programmed processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the one processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one processor and by the communication system.

596.

589 -

~~720~~. An originating device in accordance with claims ~~713~~-
595 wherein:

the one processor executes at least one application program which processes the information.

597

589

~~721~~. An originating device in accordance with claim ~~713~~ wherein:

after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail before transmission by the wireless system.

⁵⁹⁸
~~722~~. An originating processor in accordance with claim
⁵⁸⁹
~~713~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

⁵⁹⁹
~~723~~. An originating device in accordance with claim ⁵⁹⁸
~~722~~ wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

B1
Sub 021
6002-6004-6005
724. An originating device in accordance with claim 713 wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

⁶⁰¹
~~725~~. An originating device in accordance with claim ⁶⁰⁰
~~724~~ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of the permissible wireless devices in the wireless system.

Sub 022
726. An originating device in accordance with claim 713 wherein:

the wireless system broadcasts the information and an identification of the wireless device at a location in the

Sub 23
wireless system to the wireless device determined from information stored in the wireless system pertaining to a location of the wireless device in the wireless system.

603
~~727~~: An originating device in accordance with claim *589* ~~713~~

wherein:

the one processor is a PC and the programmed processor is a PC.

B
Sub 23
728. In a communication system comprising a wireless system which communication system transmits electronic mail inputted to the communication system from an originating device which executes electronic mail programming to originate the electronic mail, processors which execute electronic mail programming to function as a destination of electronic mail, and a destination processor to which the electronic mail is transmitted from the originating device and after reception of the electronic mail by the destination processor, information contained in the electronic mail and an identification of a wireless device in the wireless system are transmitted by the wireless system to the wireless device and from the wireless device to one of the processors, the wireless device and processor comprising:

a wireless receiver connected to the one processor with the processor receiving the information after the identification of the wireless device is detected by the wireless receiver in a broadcast by the wireless system.

^{605.}
~~729~~ A wireless device and processor in accordance with
⁶⁰⁴
claim ~~728~~ wherein:

the electronic mail originated by the originating device also contains an identification of the wireless device and a recipient of the electronic mail to receive the information at the one processor.

^{606.}
~~730~~ A wireless device and processor in accordance with
⁶⁰⁵
claim ~~729~~ wherein:

the identification of the wireless device is a number.

^{607.}
~~731~~ A wireless device and processor in accordance with
⁶⁰⁴
claim ~~728~~ wherein:

the originating device is a processor, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the originating device and by the communication system; and

the one processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one processor and by the communication system.

^{608.}
~~732~~ A wireless device and processor in accordance with
⁶⁰⁵
claim ~~729~~ wherein:

the originating device is a processor, executes electronic mail programming to originate electronic mail which

is wirelessly transmitted from the originating device and by the communication system; and

the one processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one processor and by the communication system.

^{609.}
~~733.~~ A wireless device and processor in accordance with claim ⁶⁰⁶~~730~~ wherein:

B7
the originating device is a processor, executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the originating device and by the communication system; and

the one processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the one processor and by the communication system.

Sub 37
734. A wireless device and processor in accordance with claims 728-733 wherein:

the one processor execute at least one application program which processes the information.

^{611.}
~~735.~~ A wireless device and processor in accordance with claim ⁶⁰⁴~~728~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

612

736. A wireless device and processor in accordance with claim ~~735~~⁶¹¹ wherein:

the deleted information is a header in the electronic mail inputted by the originating device.

Sub 035
737. A wireless device and processor in accordance with claim 728 wherein:

after reception by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

614.

738. A wireless device and processor in accordance with claim ~~737~~⁶¹³ wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

Sub 036
739. A wireless device and processor in accordance with claim 728 wherein:

the wireless system broadcasts the information and an identification of the wireless device at a location in the wireless system to the wireless device determined from information stored in the wireless system pertaining to a location of the wireless device in the wireless system.

616.

740. A wireless device and processor in accordance with claim ~~728~~⁶⁰⁴ wherein:

the one processor is a PC and the originating device is a PC.

741. A communication system comprising:

devices, each device comprising a wireless device connected to a processor which processor executes electronic mail programming to function as a destination of electronic mail, the wireless device after receiving a broadcast of information and an identification of the wireless device transmits the information to the connected processor;

a wireless system which transmits the information and the identification of the wireless device and broadcasts the information and the identification of the wireless device;

a programmed processor which executes electronic mail programming to originate the electronic mail which contains an address of a destination to which the electronic mail is transmitted and the information; and

a destination processor which receives the electronic mail and is the destination of the electronic mail; and wherein

after reception of the electronic mail by the destination processor, the information and the identification of the wireless device are transmitted to the wireless system and broadcast to the wireless device.

618.

742. A communication system in accordance with claim 741

wherein:

the electronic mail originated by the programmed processor also contains an identification of the wireless device and a recipient of the electronic mail to receive the information at the connected processor.

^{619.}
~~743.~~ A communication system in accordance with claim ~~741~~ ⁶¹⁷
wherein:

the identification of the wireless device is a number.

^{620.}
~~744.~~ A communication system in accordance with claim ~~741~~ ⁶¹⁷
wherein:

the programmed processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the connected processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the connected processor and by the communication system.

^{621.}
~~745.~~ A communication system in accordance with claim ~~742~~ ⁶¹⁸
wherein:

the programmed processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the connected processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the connected processor and by the communication system.

622.

619

~~746.~~ A communication system in accordance with claim ~~743~~ wherein:

the programmed processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the programmed processor and by the communication system; and

the connected processor executes electronic mail programming to originate electronic mail which is wirelessly transmitted from the connected processor and by the communication system.

747. A communication system in accordance with claims 741-746 wherein:

the connected processor executes at least one application program which processes the information.

624.

617

~~748.~~ A communication system in accordance with claim ~~741~~ wherein:

after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

625.

624

~~749~~. A communication system in accordance with claim ~~748~~

wherein:

the deleted information is a header in the electronic mail originated by the programmed processor.

626.

617

~~750~~. A communication system in accordance with claim ~~741~~

wherein:

the connected processor is a PC and the programmed processor is a PC.

627. A communication system in accordance with claim 741

wherein:

after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

628.

627

~~752~~. A communication system in accordance with claim ~~751~~

wherein:

the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

753. A communication system in accordance with claim 741

wherein:

the wireless system broadcasts the information and the identification of the wireless device at a location in the wireless system to the wireless device determined from



Sub D30
information stored in the wireless system pertaining to a location of the wireless device in the wireless system.

B
630
754. In a communication system comprising a wireless system which communication system transmits electronic mail inputted to the communication system from processors which execute electronic mail programming to originate the electronic mail and function as a destination of electronic mail, and a destination processor to which the electronic mail is transmitted from the processors which originate the electronic mail and after reception of the electronic mail by the destination processor, information contained in the electronic mail and identifications of wireless devices in the wireless system are transmitted by the wireless system to the wireless devices and from the wireless devices to the processors connected thereto, each of the processors comprising:

a programmed processor which executes electronic mail programming to wirelessly originate the electronic mail and to function as a wireless destination of the information, the originated electronic mail containing an address of the destination processor and the information.

631.

755. The processor in accordance with claim 754 wherein:

630
the electronic mail originated by the programmed processor also contains an identification of the wireless device and a recipient of the electronic mail to receive the information.

632.

630

~~756.~~ The processor in accordance with claim ~~754~~ wherein:
the identification of the wireless device is a
number.

633.

631

~~757.~~ The processor in accordance with claim ~~755~~ wherein:
the identification of the wireless device is a
number.

630-633

758. The processor in accordance with claims ~~754-759~~
wherein:
the programmed processor executes at least one
application program which processes the information.

635.

630

~~759.~~ The processor in accordance with claim ~~754~~ wherein:
after reception of the electronic mail by the
destination processor, the identification of the wireless
device is added to the information contained in the electronic
mail.

634.

630

~~760.~~ The processor in accordance with claim ~~754~~ wherein:
after reception of the electronic mail by the
destination processor, information is deleted from the
electronic mail is not transmitted by the wireless system.

637.

636

~~761.~~ The processor in accordance with claim ~~760~~ wherein:
the deleted information is a header in the
electronic mail originated by the programmed processor.

Sub 32

762. The processor in accordance with claim 754 wherein:
after reception of the electronic mail by the
destination processor, a check is performed to determine if
the information should be transmitted by the wireless system
to the wireless device.

639 *638*
~~763~~. The processor in accordance with claim ~~762~~ wherein:
the check is performed by a comparison of an
identification of the wireless device with identifications of
permissible wireless devices in the wireless system.

B *Sub 033*

764. The processor in accordance with claim 754 wherein:
the wireless system broadcasts the information and
the identification of the wireless device at a location in the
wireless system determined from information stored in the
wireless system pertaining to a location of the wireless
device stored in the wireless system.

765. A processor for use in a communication system
including a wireless system which transmits and receives
wireless communications including electronic mail to and from
processors, wherein the processor executes electronic mail
programming to function as an originator or destination of
electronic mail, the processor comprising:

a programmed processor which executes electronic mail
programming to wirelessly transmit electronic mail to the
communication system and wirelessly receive electronic mail
from the communication system; and wherein

Sub D33

B

669921-604544

when the programmed processor sends electronic mail to the communication system containing an address of a destination processor included in the communication system and information, the destination processor receives the information, and after receiving the information, an identification of a wireless device functioning as a wireless destination of the information and the information are transmitted by the wireless system and broadcast to the wireless device which receives the information and transmits the information to one of the processors connected thereto.

642.

641

~~766~~. A processor in accordance with claim ~~765~~ wherein:
the electronic mail originated by the programmed processor also contains an identification of the wireless device and a recipient of the electronic mail to receive the information.

643.

641

~~767~~. A processor in accordance with claim ~~765~~ wherein:
the identification of the wireless device is a number.

644.

642

~~768~~. A processor in accordance with claim ~~766~~ wherein:
the identification of the wireless device is a number.

Sub D34

769. A processor in accordance with claims 765-768 wherein:

Sub D34 [the programmed processor executes at least one application program which processes the information.

646. *641*
~~770.~~ A processor in accordance with claim ~~765~~ wherein:
after reception of the electronic mail by the destination processor, the identification of the wireless device is added to the information contained in the electronic mail.

B *647.* *641*
~~771.~~ A processor in accordance with claim ~~765~~ wherein:
after reception of the electronic mail by the destination processor, information is deleted from the electronic mail and is not transmitted by the wireless system.

648. *647*
~~772.~~ A processor in accordance with claim ~~771~~ wherein:
the deleted information is a header in the electronic mail transmitted by the programmed processor.

Sub D35 [*649*
773. A processor in accordance with claim ~~765~~ wherein:
after reception of the electronic mail by the destination processor, a check is performed to determine if the information should be transmitted by the wireless system to the wireless device.

650. *649*
~~774.~~ A processor in accordance with claim ~~773~~ wherein:
the check is performed by a comparison of an identification of the wireless device with identifications of permissible wireless devices in the wireless system.

SUBSTITUTE APPENDIX

669027" 60452460
669027" 60452460

004340 10049

004340 10049

APPENDIX

Copyright Thomas Campana, Jr. 1991

define ATT_MAIL_FILE
define DELIMITER

"TFPCOM.TIP"
"End of Telefind Network Message\r"

66902F"60455460

66902F"60455460

657227" 60455460
657227" 60455460

```

(
    case 1:
        /*      datestr = mm/dd, timestr = hh:mm      */
        sscanf(datestr,"%d/%d",&month,&day);
        /*      got year from pc      */

        t = time(NULL);
        fprintf(outfile,"Date: %s",ctime(&t));
        break;

    case 2:
        fprintf(outfile,"From: %s",buffer);
        break;

    case 3:
        fprintf(outfile,"Subject: %s",buffer);
        fprintf(outfile,"To: <Name here>\n");
        if (msg_num_opt)
            fprintf(outfile,"Message %d\n",msg_num);
        break;

    default:
        fprintf(outfile,"%s",buffer);
        break;
}
else
(
    if (line == 1)
    (
        t = time(NULL);
        fprintf(outfile,"Date: %s",ctime(&t));
        fprintf(outfile,"From: %s\n",buffer);
        fprintf(outfile,"Subject: Telefind Network Message\n");
        fprintf(outfile,"To: <Name here>\n");
        if (msg_num_opt)
        (
            fprintf(outfile,"Message %d\n",msg_num);
            fprintf(outfile,"%s",buffer+3);
        )
        else
            fprintf(outfile,"%s",buffer);
    )
    else
        fprintf(outfile,"%s",buffer);
)

if (strcmp(buffer,DELIMITER) == 0)
(
    msg_num_opt = line = attmail = 0;
)

line ++;

```

66302T 6045460
66402T 6045460

```
/*
    Copyright:      1990 TELEFIND CORP.
    Author:         MICHAEL P. PORSCHKE, SR.
                   03/13/91

    Program:        SAFARI3.C
    Purpose:        TO EXTRACT MESSAGES FROM A TELEFIND PAGER
                   VIA IN RS-232 PORT ON A PC

    Compiler:       TURBO C++ 1.0
    Memory Model:   SMALL
*/

#include <dos.h>
#include <stdio.h>
#include <conio.h>
#include <string.h>
#include <stdlib.h>
#include "safari.h"

/*          CONSTANTS          */

#define DTR_HI      0x01
#define DTR_LO      0xfe
#define RTS_HI      0x02
#define RTS_LO      0xfd
#define DSR_HI      0x20
#define RING_IN     0x40
#define CD_HI       0x80
#define FIVE_TICK   5
#define FIVE_SEC    96
#define TWELVE_SEC  220
#define LOG_FILE    "LOG"
#define INTRO_STRING "please standby, retrieving messages ..."

/*  FUNCTION PROTOTYPES  */

int beep(void);
void busyoff(void);
void busyon(void);
void dloff(void);
void dleon(void);
int link(void);
void print_message(void);
int rxdats(void);
int strobe(void);
int strobe_data(void);
unsigned ticks(void);
int timeout(unsigned start, int delay);

/*  VARIABLE DECLARATIONS  */

char pager_buffer[31];
int com_base, control_reg, status_reg, log_flag;
FILE *log_file;

void main(int run_arg, char **args)
{
    unsigned start;
    int restart, x;

    com_base = 0x3f8; /* use com 1 unless command line denotes otherwise */

    /* get command line arguments */
}
```


0045403 120609
009027 0055460

```
/* all command line arguments begin with a single '-' and
must be separated by a single space between each other
and the program name

-1 Use COM port 1
-2 Use COM port 2
-f Log all activity to a file named LOG */

if (num_arg > 1)
{
    for (x=1; x<num_arg; x++)
    {
        if (strcmp(args[x], "-1") == 0)
            com_base = 0x3f8;
        if (strcmp(args[x], "-2") == 0)
            com_base = 0x2f8;
        if (strcmp(args[x], "-f") == 0)
            log_flag = 1;
    }
}

if (log_flag)
    if ((log_file = fopen(LOG_FILE, "wt")) == NULL)
        printf("Unable to open LOG\n");

control_reg = com_base + 4;
status_reg = com_base + 6;

clrscr();

if (link() == 0) /* is pager attached ? */
{
    printf("Please attach Message Receiver \n");
    exit(0);
}

busyon(); /* start busy at logic high */

if (log_flag)
    fprintf(log_file, "Initiating process \n");
printf("%s\n", INTRO_STRING);
delay(); /* push display button */
sleep(2);
do
{
    start = ticks();
    restart = 0;
    do
    {
        if (beep())
        {
            print_message();
            restart = 1;
            start += TWELVE_SEC;
            break;
        }
    }
    /* hold display button for 12 seconds */
    while(! timeout(start, TWELVE_SEC));
}
while(restart);

delay(); /* release the display button */
if (log_flag)
{
    fprintf(log_file, "Process Complete \n");
}
```

09455409.120699
669027.6055460

```
fclose(log_file);
}

/*      pager beep      */
int beep(void)
{
    /*      accesses the RI line via the Status Register
        which is activated when the pager beeps      */
    unsigned start;

    start = ticks();
    while ( ! timeout(start,FIVE_TICK))
    {
        if (((inportb(status_reg) & RING_IN) == 0 )
            return(1);
        }
    }
    return(0);
}

/*      busyon & busyoff toggle the DTR line via the
    Control Register to strobe in data from the pager      */
void busyoff(void)
{
    outportb(control_reg,inportb(control_reg) | DTR_HI);
}

void busyon(void)
{
    outportb(control_reg,inportb(control_reg) & DTR_LO);
}

/*      dison & disoff toggle the RTS line via the Control Register
    to simulate the pressing of the display button on the pager      */
void dison(void)
{
    outportb(control_reg,inportb(control_reg) | RTS_HI);
}

void disoff(void)
{
    outportb(control_reg,inportb(control_reg) & RTS_LO);
}

int link(void)
{
    /*      accesses the CD line via the Status Register
        which is logic high when pager is connected      */
    if (((inportb(status_reg) & CD_HI) == 0)
        return(0);
    }
    return(1);
}

void print_message(void)
{
    FILE *file;
    unsigned start;
    int x,y=0,z=0,chr,bit;
```

```

busyoff(); /* ready to accept pager data */
/* read until end code received */
while (chr != 3)
{
    chr = 0;
    start = tdate();

    /* wait for start bit */

    do
    {
        bit = strobe();
        if (bit == 0)
            break;
    }
    while (!timeout(start,FIVE_SEC));

    if (bit)
    {
        if (log_flag)
            fprintf(log_file,"Transmission Error, recheck connection\n");
        disoff();
        exit(0);
    }

    /* strobe out 8 bit data */

    for (x=1; x<9; x++)
    {
        chr <= 1;
        chr += bit * strobe_data();
    }

    /* clear out stop bits */
    for (x=1; x<3; x++)
    {
        strobe_data();
    }

    /* extract start and end codes from message

    pager signon      02, 10, 00, 33
    pager signoff     03 */

    if ((y > 3) && (chr != 3))
    {
        /* pager characters 96 and 97 are converted to
        0xFA and 0xFB to display on pager */

        if (chr == 0xFA) /* convert to CR */
            chr = '\n';
        if (chr == 0xFB) /* convert to TAB */
            chr = 0x09;

        pager_buffer[z] = chr;
        z ++;
    }
    y ++;
}

pager_buffer[z] = '\0'; /* null terminate */

busyon(); /* finished receiving data */

```

0945409-120699

66902T 6045409

```

if (log_file)
    fprintf(log_file, "%s\n", pager_buffer);

if ((file = fopen(ATT_EMAIL_FILE, "at")) == NULL)
    fprintf(log_file, "Unable to open TFWOSCK.TMP\n");
else
{
    fprintf(file, "%s\n", pager_buffer);
    fprintf(file, "%s", DELIMITER);
    fclose(file);
}

start = ticks();
while(timeout(start, FIVE_SEC))
{
    /* wait for erase beep */
    if (beep()) break;
}
sleep(1); /* wait one more second */
}

int rdata(void)
{
    /* accesses the DSR line via the Status Register
       which returns the bits value */

    if ((inportb(status_reg) & DSR_M1)
        return(0);
    return(1);
}

int strobe(void)
{
    int bit;

    busyon();
    delay(1);
    busyoff();
    delay(4);
    bit = rdata();
    return(bit);
}

int strobe_data(void)
{
    int bit;

    busyon();
    delay(2);
    bit = rdata();
    busyoff();
    delay(1);
    return(bit);
}

unsigned ticks(void)
{
    /* returns timer ticks (approx. 18.2/sec)
       using only lower registers */

    union REGS in, out;

    in.x.ax = 0x0;
    int86(0x10, &in, &out);
    return(out.x.ax);
}

```

0045400 4069

0045400 4069

```

}
int timeout(unsigned start, int delay)
{
    /*      used for timing events of up to approx. 1 hour.
           used in conjunction w/ticks()      */

    unsigned current;

    current = ticks();
    if (start <= current && (start + delay) < current)
        return(1);
    if (start > current && (start + 65535 + delay) < current)
        return(1);
    return(0);
}

```

Copyright Telefind Corporation 1990

```
/* mark the end of the command line you built,so you can add ending
delimiter */
sys_command[i] = NULL;
/* add the ending quote for the users message so shell wont
interepert special characters */
strcat(sys_command, "\\");
/* execute command you built */
system(sys_command);

printf("sending message: %s\n", sys_command);

}
else {
    if(strlen(mesg) == 0 ) {
        return(0);
    }
    /* print error for invalid message length */
    printf("telemail error: invalid message length: %s\n", mesg);
    return(0);
}

return(i);
}

/*****
*
* function: getline(hold-buffer, input-file-pointer)
* arguments: pointer to buffer where line read will be heald,
*            file pointer to input file
* description: reads 1 line of text from the input line and stores the
*            line read into the buffer passed.
* returns: -1 if EOF or number of characters read in
*
*****/
getline(buff, fp)
char *buff;
FILE *fp;
{
    int ch, cnt;

    /* keep on reading characetr from file so long as end of file not
    reached or char is the end of line */
    for(cnt = 0; ((ch = fgetc(fp)) != EOF) && ch != '\n'; cnt++) {
        /* MOD BY OT 11/29/90 convert tab to space */
        /* convert tabs to single space */
        if(ch == 9) {
            ch = ' ';
        }
        /* MOD BY OT 11/29/90 dont allow control char */
        /* only load in ascii characters */
        if(isprint(ch) != 0) {
            buff[cnt] = ch;
        }
        else {
            /* turn control characters to spaces */
            buff[cnt] = ' ';
        }
    }
    /* mark the end of the buffer you built */
    buff[cnt] = '\0';
}
```

0045409 120699
009027 0045409

66902T 60455460

66902T 60455460

```
/* since your just starting clear the message area */
memset(mesg, NULL, MAXMSGLEN);

/* keep on geting lines from the file until you reach end of file */
while(getline(buff, fp) != -1) {

    /* every mail message start with the word "From " */
    if(strncmp(buff, "From ", 5) == 0) {
        /* set flag telling you are currently going thru mail header
           so you dont add it to the message */
        in_header = 1;
        /* call routine to the last message if any exists */
        send_mesg(mesg);
        continue;
    }

    /* a mail header end with the following string */
    if(strncmp(buff, "Content-Length:", 15) == 0) {
        /* turn off flag so you know you are no longer in mail
           message header */
        in_header = 0;
        /* clear the old message since this is a new one */
        memset(mesg, NULL, MAXMSGLEN);
        continue;
    }

    /* if the line you are now reading in not part of the mail header
       add it to the message */
    if(in_header == 0) {
        strljust(buff, 512);
        strtrim(buff);
        /* make sure you dont add more than the message length */
        if( (strlen(buff) + strlen(mesg)) < MAXMSGLEN) {
            strcat(mesg, " ");
            strcat(mesg, buff);
        }
    }
}

/* end of read line while */

/* send the last message in the file */
send_mesg(mesg);

}
```


09453409 120699
09453409 120699

```
\\/******
*
*   Program name: telemail.c   network mail pickup
*   Description: program searches the passed "mail" file and extracts
*                 the messages from it. a message is delimited by the words
*                 "message length" and "From ". these messages are then
*                 out on the telefind network. non ascii characters
*                 are skipped and invalid messages are displayed to the
*                 standard output.
*   author: Oren Tavory
*   site: telefind.corp
*   date: 11/25/90
*   modification history:
*       11/29/90 MOD BY OT fix problem of tabs being sent to network
*                   by converting tabs to a space char
*       11/29/90 MOD BY OT fix problem of control characters being
*                   passed if the message
*
*****/
#include <stdio.h>
#include <string.h>
#include <ctype.h>

#define MAXMSGLEN 512
#define MAXLINELEN 512

void main(argc, argv)
int argc;
char *argv[];
{
    FILE *fp;
    char *buff;
    char *mesg;
    int in_header;

    /* make sure user passed filename to be converted */
    if(argc != 2) {
        printf("telemail ERROR: Usage: telemail mail-filename\n");
        exit(1);
    }

    /* open the mail file */
    if((fp = fopen(argv[1], "r")) == NULL) {
        printf("telemail error: cant open mail file %s\n", argv[1]);
        exit(2);
    }

    /* allocate need buffer that will hold each line of the file */
    if((buff = (char *) malloc( MAXLINELEN * sizeof(char))) == NULL) {
        printf("telemail error: cant allocate memory for buffer\n");
        exit(3);
    }

    /* allocate buffer for message to be stored */
    if((mesg = (char *) malloc( MAXMSGLEN * sizeof(char))) == NULL) {
        printf("telemail error: cant allocate memory for message\n");
        exit(4);
    }
}
```

66902T" 60455460
66902T" 60455460

```
    if(ch == EOF) {  
        return (-1);  
    }  
    else {  
        return(cnt);  
    }  
}
```

Claims

1. An electronic mail system for transmitting information from one of a plurality of originating processors to at least one of a plurality of destination processors during operation comprising:

5 at least one gateway switch, a gateway switch storing information received from one of the at least one originating processor prior to transmission of the information to the at least one destination processor;

10 a RF information transmission network for transmitting stored information received from one of the at least one gateway switch by RF transmission to at least one destination processor;

15 at least one interface switch, an interface switch connecting a gateway switch to the RF transmission network and transmitting stored information received from one of the at least one gateway switch to the RF information transmission network; and wherein

20 the information is transmitted to a receiving interface switch by the electronic mail system in response to an address of the receiving interface switch which has been added to the information originated by the originating processor by either the
25 originating processor or gateway switch and the information is transmitted from the receiving interface switch to the RF information transmission network with an address of the destination processor to receive the information which has been added by either the
30 originating processor, a gateway switch or the receiving interface switch.

2. An electronic mail system in accordance with claim 1 wherein:

the receiving interface switch removes information added by the electronic mail system to the information originated by the originating processor from the stored information received from one of the at least one gateway switch and adds information used by the RF information transmission network during transmission of the information to the information originated by the originating processor to a RF receiver in the RF information transmission network which receives the information and relays it to the destination processor.

3. An electronic mail system in accordance with claim 1 wherein:

the address of the destination processor is an identification number of a RF receiver in the RF information transmission network which receives the information and relays it to the destination processor; and

the receiving interface switch stores information which has been stored by at least one gateway switch that is received from a plurality of originating processors, assembles the information from a plurality of originating processors into a packet and transmits the packet to the RF information transmission network.

5

10

15

25

30

the receiving interface switch stores information which has been stored by at least one gateway switch that is received from a plurality of originating processors, assembles the information from a plurality of originating processors into a packet and

6. An electronic mail system in accordance with claim 5 wherein the RF information transmission network comprises:

the RF information transmission network transmits the disassembled information, including the identification number of the RF receiver relaying information to destination processor to a switch in the RF information transmission network storing a file identified by the identification number and any destination of the RF receiver in the RF information transmission network to which the information and identification number is to be transmitted by the RF information transmission network and adds any destination of the RF receiver to the information and the RF information transmission network in response to any added destination transmits the information and identification number to the destination for RF broadcast to the RF receiver for relaying to the destination processor.

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a

different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

8. An electronic mail system in accordance with claim 2 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

9. An electronic mail system in accordance with claim 3 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

10. An electronic mail system in accordance with claim 4 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

11. An electronic mail system in accordance with claim 5 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

12. An electronic mail system in accordance with claim 6 wherein:

the electronic mail system also transmits information between an originating processor and at least one destination processor through either a public or private switch telephone network without transmission by the RF information transmission network with the destination processor being addressed by a different address during transmission to the destination processor when using the public switch telephone network transmission network than during transmission by the RF information transmission network.

13. An electronic mail system in accordance with claim 1 further comprising:

a RF receiver connectable to the destination processor and in response to connection of the RF receiver to the destination processor the RF receiver transfers information stored in a memory of the RF receiver received from the originating processor to the destination processor;

a number of originating processors is greater than a number of interface switches; and

a plurality of originating processors also function as destination processors with a RF receiver connected thereto.

14. An electronic mail system in accordance with claim 1 wherein:

the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

66902T 60455460
66902T 60455460

the address of the receiving interface switch is added by the originating processor.

the address of the destination processor is an identification number of a RF receiver receiving the information and relaying the information to the destination processor and is added to the information originated by the originating processor by the originating processor.

the address of the destination processor is an identification number of a RF receiver receiving the information and relaying the information to the destination processor and is added to the information originated by the originating processor by the gateway switch.

the address of the destination processor is an identification number of a RF receiver receiving the information and relaying the information to the destination processor and is added to the information originated by the originating processor by the receiving interface switch.

19. An electronic mail system in accordance with claim 2 wherein:

the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

20. An electronic mail system in accordance with claim 2 wherein:

the address of the receiving interface switch is added by the originating processor.

21. An electronic mail system in accordance with claim 2 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the originating processor.

22. An electronic mail system in accordance with claim 2 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the gateway switch.

23. An electronic mail system in accordance with claim 2 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

24. An electronic mail system in accordance with claim 3 wherein:

the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

25. An electronic mail system in accordance with claim 13 wherein:

the address of the receiving interface switch is added by the originating processor.

5 26. An electronic mail system in accordance with claim 13 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the originating processor.

10 27. An electronic mail system in accordance with claim 13 wherein:

the identification number of the RF receiver is added to the information originated by the originating processor by the gateway switch.

15 28. An electronic mail system in accordance with claim 13 wherein:

20 the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

29. An electronic mail system in accordance with claim 4 wherein:

25 the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

30. An electronic mail system in accordance with claim 4 wherein:

the address of the receiving interface switch is added by the originating processor.

66902T 60455460

66902T 60455460

5

10

15

20

25

the address of the receiving interface switch is added by the originating processor.

36. An electronic mail system in accordance with claim 5 wherein:

5 the identification number of the RF receiver is added to the information originated by the originating processor by the originating processor.

37. An electronic mail system in accordance with claim 5 wherein:

10 the identification number of an RF receiver is added to the information originated by the originating processor by the gateway switch.

38. An electronic mail system in accordance with claim 5 wherein:

15 the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

39. An electronic mail system in accordance with claim 6 wherein:

20 the address of the receiving interface switch is added to the information originated by the originating processor by a gateway switch.

40. An electronic mail system in accordance with claim 6 wherein:

25 the address of the receiving interface switch is added by the originating processor.

41. An electronic mail system in accordance with claim 6 wherein:

30 the identification number of the RF receiver is added to the information originated by the originating processor by the originating processor.

SECRET

SECRET

42. An electronic mail system in accordance with claim 6 wherein:

5 the identification number of the RF receiver is added to the information originated by the originating processor by the gateway switch.

43. An electronic mail system in accordance with claim 6 wherein:

10 the identification number of the RF receiver is added to the information originated by the originating processor by the receiving interface switch.

44. An electronic mail system in accordance with claim 14 wherein:

15 the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the
20 address of the receiving interface switch.

45. An electronic mail system in accordance with claim 15 wherein:

25 the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

0945403 10633
009027 60455460

46. An electronic mail system in accordance with claim 15 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

47. An electronic mail system in accordance with claim 16 wherein:

the identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

48. An electronic mail system in accordance with claim 16 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

49. An electronic mail system in accordance with claim 17 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

50. An electronic mail system in accordance with claim 18 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

51. An electronic mail system in accordance with claim 19 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

667027" 6045460

669027" 6045460

5

10

15

20

25

30

55. An electronic mail system in accordance with claim 21 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

56. An electronic mail system in accordance with claim 22 wherein:

5 the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

10

57. An electronic mail system in accordance with claim 23 wherein:

15 the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

20

58. An electronic mail system in accordance with claim 24 wherein:

25 the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

SECRET
SECRET

59. An electronic mail system in accordance with claim 25 wherein:

5 the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

60. An electronic mail system in accordance with claim 25 wherein:

10 the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the
15 address of the receiving interface switch.

61. An electronic mail system in accordance with claim 26 wherein:

20 an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

62. An electronic mail system in accordance with claim 26 wherein:

25 the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to
30 the information as the identification number.

63. An electronic mail system in accordance with claim 27 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

64. An electronic mail system in accordance with claim 28 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

65. An electronic mail system in accordance with claim 29 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

66. An electronic mail system in accordance with claim 30 wherein:

the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

67. An electronic mail system in accordance with claim 30 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

68. An electronic mail system in accordance with claim 31 wherein:

an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

69. An electronic mail system in accordance with claim 31 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

70. An electronic mail system in accordance with claim 32 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

71. An electronic mail system in accordance with claim 33 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

72. An electronic mail system in accordance with claim 34 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

73. An electronic mail system in accordance with claim 35 wherein:

5 the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

74. An electronic mail system in accordance with claim 35 wherein:

10 the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the
15 address of the receiving interface switch.

75. An electronic mail system in accordance with claim 36 wherein:

20 an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

76. An electronic mail system in accordance with claim 36 wherein:

25 the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to
30 the information as the identification number.

669027 6045460
669027 6045460

77. An electronic mail system in accordance with claim 37 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

78. An electronic mail system in accordance with claim 38 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

79. An electronic mail system in accordance with claim 39 wherein:

the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the address of the receiving interface switch.

80. An electronic mail system in accordance with claim 40 wherein:

5 the address of the receiving interface switch is added by an inputting of the address of the receiving interface switch along with an identification of the destination processor.

81. An electronic mail system in accordance with claim 40 wherein:

10 the address of the receiving interface switch is added by matching an identification of the destination processor with a stored identification of a destination processor and adding an address of an interface switch stored with the matched identification of the destination processor to the information as the
15 address of the receiving interface switch.

82. An electronic mail system in accordance with claim 41 wherein:

20 an identification number is added to the information originated by the originating processor by inputting the identification number to the originating processor.

83. An electronic mail system in accordance with claim 41 wherein:

25 the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to
30 the information as the identification number.

66902T 6045460
66902T 6045460

84. An electronic mail system in accordance with claim 42 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

85. An electronic mail system in accordance with claim 43 wherein:

the identification number is added to the information originated by the originating processor by matching an identification of the destination processor with a stored identification of a destination processor and adding an identification number stored with the matched identification of the destination processor to the information as the identification number.

00453403 120659
00453403 120659

ADD
AS

ADD
BI

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"ELECTRONIC MAIL SYSTEM WITH RF COMMUNICATIONS TO MOBILE PROCESSORS"

the specification of which (check one)

☒

is attached hereto.

☐

was filed on _____

as Application Serial No. _____

and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

None

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

(Number)

(Country)

(Day/Month/Year Filed)

☐

Yes

☐

No

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

None

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

I hereby appoint as principal attorneys; Donald R. Antonelli, Reg. No. 22,929; David T. Terry, Reg. No. 20,178; Melvin Kraus, Reg. No. 22,466; Stanley A. Wal, Reg. No. 26,432; William I. Solomon, Reg. No. 28,565; Gregory E. Montone, Reg. No. 28,141; Ronald J. Shore, Reg. No. 28,577; Donald E. Stout, Reg. No. 26,422; Alan E. Schiavelli, Reg. No. 32,087 and James N. Dresser, Reg. No. 22,973 to prosecute and transact all business connected with this application and any related United States application and international applications. Please direct all communications to the following address:

Antonelli, Terry, Stout & Kraus
Suite 600
1919 Pennsylvania Avenue, N.W.
Washington, D.C. 20006
Telephone: (202) 828-0300

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

66922T 60455460

| | (Full Name) | (Signature) |
|---|--|-------------------------------|
| Date <u>May 17, 1991</u> | Inventor <u>Thomas J. Campana, Jr.</u> | <u>Thomas J. Campana, Jr.</u> |
| Residence <u>Same As Post Office Address</u> | Citizenship <u>U.S.</u> | |
| Post Office Address <u>3836 West 86th Street, Chicago, Illinois 60652</u> | | |
| Date <u>5-17-91</u> | Inventor <u>Michael P. Ponschke</u> | <u>Michael P. Ponschke</u> |
| Residence <u>Same As Post Office Address</u> | Citizenship <u>U.S.</u> | |
| Post Office Address <u>212 Tara Drive, Lockport, Illinois 60441</u> | | |
| Date <u>5-17-91</u> | Inventor <u>Gary F. Thelen</u> | <u>Gary F. Thelen</u> |
| Residence <u>Same As Post Office Address</u> | Citizenship <u>U.S.</u> | |
| Post Office Address <u>16 Fox Lane, Palos Park, Illinois 60464</u> | | |
| Date _____ | Inventor _____ | |
| Residence _____ | Citizenship _____ | |
| Post Office Address _____ | | |
| Date _____ | Inventor _____ | |
| Residence _____ | Citizenship _____ | |
| Post Office Address _____ | | |
| Date _____ | Inventor _____ | |
| Residence _____ | Citizenship _____ | |
| Post Office Address _____ | | |
| Date _____ | Inventor _____ | |
| Residence _____ | Citizenship _____ | |
| Post Office Address _____ | | |
| Date _____ | Inventor _____ | |
| Residence _____ | Citizenship _____ | |
| Post Office Address _____ | | |
| Date _____ | Inventor _____ | |
| Residence _____ | Citizenship _____ | |
| Post Office Address _____ | | |

Applicant or Patentee: THOMAS J. CAMPANA, JR. et al
Serial or Patent No.: _____ Attorney's Docket No.: 780.29643X00
Filed or Issued: May 20, 1991
For: ELECTRONIC MAIL SYSTEM WITH RF COMMUNICATIONS TO MOBILE PROCESSORS

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(f) and 1.27(b)) - INDEPENDENT INVENTOR

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled "Electronic Mail System With RF Communications to Mobile Processors" described in

☒ [X] the specification filed herewith.

☐ [] Application Serial No.: _____, filed: _____.

☐ [] Patent No.: _____, issued: _____.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

☐ [] no such person, concern, or organization.

☒ [X] persons, concerns, or organizations listed below.*

*NOTE: Separate verified statements are required from each named person, concern, or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27).

FULL NAME: Thomas J. Campana, Jr.

ADDRESS: 3836 West 86th Street, Chicago, Illinois 60652

☒ [X] INDIVIDUAL ☐ [] SMALL BUSINESS CONCERN ☐ [] NONPROFIT ORGANIZATION

FULL NAME: _____

ADDRESS: _____

☐ [] INDIVIDUAL ☐ [] SMALL BUSINESS CONCERN ☐ [] NONPROFIT ORGANIZATION

FULL NAME: _____

ADDRESS: _____

☐ [] INDIVIDUAL ☐ [] SMALL BUSINESS CONCERN ☐ [] NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

THOMAS J. CAMPANA, JR.
NAME OF INVENTOR

Thomas J. Campana, Jr.
Signature of Inventor

May 17 1991
Date

MICHAEL P. PONSCHKE
NAME OF INVENTOR

Michael P. Ponschke, Sr.
Signature of Inventor

5-17-91
Date

GARY F. THELEN
NAME OF INVENTOR

Gary F. Thelen
Signature of Inventor

5-17-91
Date

0445403 1099

0445403 1099

SUPPLEMENTAL DECLARATION FOR PATENT APPLICATION

As the below named inventors, we hereby declare that:

Our residence, post office address and citizenship are as stated below next to our names, we believe that we are an original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"ELECTRONIC MAIL SYSTEM WITH RF COMMUNICATIONS TO MOBILE PROCESSORS AND METHOD OF OPERATION THEREOF"

the specification of which was filed on May 20, 1991 as application Serial No. 07/702,939 and as amended in amendments attached hereto including claims 86-176.

We hereby state that we have reviewed and understand the contents of the amendments to the above-identified specification, and newly submitted claims 86-176, as attached.

We acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

We hereby declare that all statements made herein of my our knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Date: June 15, 94

Inventor: Thomas J. Campana, Jr.

Residence: Same As Post Office Address
Post Office Address: 3836 West 86th Street
Chicago, Illinois 60652

Date: 6-15-94

Inventor: Michael P. Ponschke
Michael P. Ponschke

Residence: Same As Post Office Address
Post Office Address: 212 Tara Drive
Lockport, Illinois 60441

Date: 7-1-94

Inventor: Gary F. Thelen
Gary F. Thelen

Residence: Same As Post Office Address
Post Office Address: 16 Fox Lane
Palos Park, Illinois 60464

6455405 10455405

780.29643CX3
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Thomas J. CAMPANA, Jr. et al
Serial No.: 09/161,462
Filed: September 28, 1998
For: ELECTRONIC MAIL SYSTEM WITH RF
COMMUNICATIONS TO MOBILE PROCESSORS
Group: 2744
Examiner: William Trost

SECOND PRELIMINARY AMENDMENT

Assistant Commissioner
for Patents
Washington, D. C. 20231

May 25, 1999

Sir:

Prior to examination of the above-identified application,
please amend the specification as follows:

IN THE SPECIFICATION:

Page ii, line 13, please modify the insert added by the
first Preliminary Amendment of September 28, 1998 as follows.

after "Serial No. 08/844,957" and before the
period, insert the following:

--, filed April 23, 1997, now U.S. Patent No. 5,819,172; which
is a continuation of United States Patent Application Serial
No. 08/443,430, filed May 18, 1995, now U.S. Patent 5,625,670;
which is a continuation of United States Patent Application
Serial No. 07/702,939, filed May 20, 1991, now U.S. Patent
5,436,960.--

Jc678 U.S. PTO
09/455409
12/06/99

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

780.29643CX2

Applicants: Thomas J. CAMPANA, Jr. et al
Serial No.: 08/844,957
Filed: April 23, 1997
For: ELECTRONIC MAIL SYSTEM WITH RF
COMMUNICATIONS TO MOBILE PROCESSORS
Group: 2608 (Previous)
Examiner: William Trost (Previous)

JC678 U.S. PTO

09/455409



**PRELIMINARY AMENDMENT AND
INFORMATION DISCLOSURE STATEMENT**

Assistant Commissioner
for Patents
Washington, D. C. 20231

September 4, 1997

Sir:

Prior to examination of the above-identified application,
please amend the specification as follows:

IN THE SPECIFICATION:

Page i (before Page 1), the Appendix, line 12, change
"10-14" to --10-12--.

In the actual Appendix pages, delete the original 15
pages of the Appendix as filed on May 20, 1991 and insert a
substitute Appendix which is attached hereto.

Page ii (in the Cross-Reference to Related Applications),
line 6, delete the blank line "_____" and insert therefor
--07/702,319--;

line 2, delete "which are";

line 3, delete "filed on even date herewith";

659027 00000000